

# Safety Data Sheet

Dry Moly

## SECTION I - IDENTIFICATION

**PRODUCT IDENTIFIER:** Dry Moly  
**PRODUCT CODE:** 555000015-16AR  
**RECOMMENDED USE:** Lubricant  
**RESTRICTIONS ON USE:** None known.  
**COMPANY NAME:** Rope, Soap'n Dope  
**COMPANY ADDRESS:** 1025 Petroleum Parkway, Broussard, LA 70518  
**COMPANY PHONE:** 337-233-4841  
**EMERGENCY PHONE:** 800-255-3924

## SECTION II – HAZARDS IDENTIFICATION


**CLASSIFICATION:** Flammable Aerosol: Category 1  
Gases Under Pressure: Compressed Gas  
Skin Irritant: Category 2  
Eye Irritant: Category 2A  
Reproductive Toxicity: Category 2  
Specific Target Organ Toxicity (Single Exposure): Category 3  
Specific Target Organ Toxicity (Repeated Exposure): Category 2

**HAZARD STATEMENT(S): DANGER:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to central nervous system (CNS), liver, kidneys and respiratory system through prolonged or repeated exposure.

This product contains the following percentage of chemicals of unknown toxicity: N/A

**PRECAUTIONARY STATEMENTS:** Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Obtain, read and follow all safety instructions before use. Wash hands thoroughly after handling. Wear protective gloves and eye protection. Do not eat, drink or smoke when using this product. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If exposed or concerned: Get medical advice or attention immediately. Do not breathe mist, vapor and spray. Use only outdoors or in a well-ventilated area. Dispose of contents and container in accordance with local, state and federal regulations.

**SYMBOL:**



**HAZARDS NOT OTHERWISE CLASSIFIED:** N/A

## SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Acetone	67-64-1	15-40%
Toluene	108-88-3	15-40%
Propane	74-98-6	10-30%
Butane	106-97-8	10-30%

**Trade Secret Information:** A specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## SECTION IV - FIRST AID MEASURES

**EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Seek medical attention if irritation persists.

# Safety Data Sheet

## Dry Moly

- INGESTION:** Rinse mouth out with water. Do not induce vomiting unless directed by medical authority. Keep head below hips if vomiting occurs. Seek immediate medical attention. Aspiration hazard. Never give anything by mouth to an unconscious person.
- INHALATION:** Move to fresh air. If breathing is difficult, administer oxygen. If not breathing administer artificial respiration or at any sign of loss of consciousness seek immediate medical attention.
- SKIN:** Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation persists.
- ACUTE HEALTH HAZARDS:** Causes skin irritation including redness, burning and drying/cracking. Causes eye irritation including redness, tearing, and pain. Inhalation of vapors may cause nausea, dizziness and drowsiness. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.
- CHRONIC HEALTH HAZARDS:** May cause damage to the following organs: kidneys, liver, respiratory, reproductive and central nervous systems. Repeated exposure to toluene, in combination with constant loud noise, can cause hearing loss and dizziness. Breathing high levels of toluene during pregnancy has been shown to result in children with birth defects and to retard mental abilities and growth.
- NOTE TO PHYSICIAN:** Treatment of overexposure should be directed at the control of symptoms and the clinical condition. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

### SECTION V – FIRE-FIGHTING MEASURES

- EXTINGUISHING MEDIA:** Dry chemical, carbon dioxide, foam, and water spray or fog.
- UNSUITABLE EXTINGUISHING MEDIA:** Water jets or streams.
- SPECIAL FIRE FIGHTING PROCEDURES:** Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers.
- UNUSUAL FIRE AND EXPLOSION HAZARDS:** EXTREMELY FLAMMABLE. Vapors may form explosive mixtures with air. Vapors heavier than air will settle in low lying areas and may travel to source of ignition and flash back. Keep away from heat, sparks, open flames and other sources of ignition.
- HAZARDOUS COMBUSTION PRODUCTS:** Oxides of carbon, hydrocarbons.

### SECTION VI – ACCIDENTAL RELEASE MEASURES

- PERSONAL PROTECTIVE EQUIPMENT:** Refer to section VIII for proper Personal Protective Equipment.
- SPILL:** Eliminate all sources of ignition. Clean up using rag or use some non-combustible material like vermiculite, sand or earth. Prevent spill from entering sewers, storm drains and natural waterways. Place waste in proper containers for disposal.
- WASTE DISPOSAL:** Dispose of in accordance with local, state and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container.
- RCRA STATUS:** Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

### SECTION VII – HANDLING AND STORAGE

- HANDLING AND STORAGE:** Wear proper personal protective equipment when using this product. Avoid contact with skin, eyes and clothing. Use only with adequate ventilation. Do not inhale mist or vapor. Do not use or store with strong oxidizers. Vapors may collect in low-lying areas. Protect from sunlight. Store in a well ventilated area. Do not expose to temperatures exceeding 50 °C/122 °F. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling.
- OTHER PRECAUTIONS:** Keep out of the reach of children. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not taste or swallow. Read and follow the directions on the product label. They are the best guide to using the product in the most effective manner. The label also gives you the necessary safety precautions to protect your health.
- INCOMPATIBILITY:** Some plastics, strong oxidizing agents, acids, caustics, alkalis and chemically active metals.

### SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Acetone	1000 ppm	250 ppm
Toluene	200 ppm	20 ppm
Propane	1000 ppm	1000 ppm
Butane	Not Established	1000 ppm

**ENGINEERING CONTROLS / VENTILATION:** Use only outdoors or in a well-ventilated area.

**RESPIRATORY PROTECTION:** Not required with normal use. Wear NIOSH/MSHA approved respiratory protection if exposure limits are exceeded.

# Safety Data Sheet

## Dry Moly

**PERSONAL PROTECTIVE EQUIPMENT:** Safety glasses/goggles, chemical resistant gloves and synthetic apron.

**ADDITIONAL MEASURES:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective clothing to prevent repeated or prolonged contact with product. No smoking or open flames. Avoid contact with skin or eyes and avoid breathing vapors. Wash hands after use. If clothing becomes contaminated, immediately remove and wash.

### SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE:** Black Soft Misting Cone

**ODOR:** Solvent.

**ODOR THRESHOLD:** N/D

**pH:** N/A

**MELTING POINT/FREEZING POINT:** N/D

**INITIAL BOILING POINT AND BOILING RANGE:** N/D

**FLASH POINT:** N/D

**EVAPORATION RATE:** N/D

**FLAMMABILITY (solid/gas):** Extremely flammable aerosol.

**UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:**

**LOWER FLAMMABILITY LIMIT:** N/D

**UPPER FLAMMABILITY LIMIT:** N/D

**EXPLOSIVE LIMIT LOWER (%):** N/D

**EXPLOSIVE LIMIT UPPER (%):** N/D

**VAPOR PRESSURE (mm Hg):** N/D

**VAPOR DENSITY (AIR=1):** N/D

**RELATIVE DENSITY (H<sub>2</sub>O=1):** 0.88-0.92 @ 77 °F (25 °C)

**SOLUBILITY(IES):** Negligible.

**PARTITION COEFFICIENT: n-OCTANOL/WATER (K<sub>ow</sub>):** N/D

**AUTOIGNITION TEMPERATURE:** N/D

**DECOMPOSITION TEMPERATURE:** N/D

**VISCOSITY:** N/D

### SECTION X – STABILITY AND REACTIVITY

**REACTIVITY:** None known.

**CHEMICAL STABILITY:** Stable.

**POSSIBLE HAZARDOUS REACTIONS:** None known.

**CONDITIONS TO AVOID:** Excess heat, open flame, sparks, electric equipment, ignition sources and incompatible materials. Avoid use in confined areas.

**INCOMPATIBLE MATERIALS:** Some plastics, strong oxidizing agents, acids, caustics, alkalis and chemically active metals.

**HAZARDOUS DECOMPOSITION PRODUCTS:** None known.

### SECTION XI – TOXICOLOGICAL INFORMATION

**TOXICOLOGICAL INFORMATION:** **Acetone** (67-64-1): LD<sub>50</sub> (Oral, Rat) 5800 mg/kg; LD<sub>50</sub> (Oral, Mouse) 3000 mg/kg; LD<sub>50</sub> (Oral, Rabbit) 5340 mg/kg; LC<sub>50</sub> (Inhalation, Rat, 8h) 50100 mg/m<sup>3</sup>; LC<sub>50</sub> (Inhalation, Mouse, 4h) 44,000 mg/m<sup>3</sup>. **Toluene** (108-88-3): LD<sub>50</sub> (Oral, Rat) > 2000 mg/kg; LD<sub>50</sub> (Dermal, Rabbit) > 8000 mg/kg; LC<sub>50</sub> (Inhalation, Rat) > 12.5 mg/L.

**ROUTES OF ENTRY:** Eyes, Ingestion, Skin

**EYES:** Redness, irritation, causes temporary corneal opacity.

**INGESTION:** Not a likely route of exposure under normal product handling conditions. May cause nausea, diarrhea, vomiting, depending on the amount ingested.

**INHALATION:** May cause dizziness, nausea, central nervous system (CNS) effects.

**SKIN:** Causes irritation, redness, itching, and pain. Prolonged contact may cause defatting of the skin and dermatitis. May be harmful if absorbed through the skin.

**MEDICAL CONDITION AGGRAVATED:** Pre-existing conditions of the skin, liver, kidneys, central nervous system (CNS) and respiratory system.

**ACUTE HEALTH HAZARDS:** Causes skin irritation including redness, burning and drying/cracking. Causes eye irritation including redness, tearing, and pain. Inhalation of vapors may cause nausea, dizziness and drowsiness. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

**CHRONIC HEALTH HAZARDS:** May cause damage to the following organs: kidneys, liver, respiratory, reproductive and central nervous systems. Repeated exposure to toluene, in combination with constant loud noise, can cause hearing loss and dizziness.

# Safety Data Sheet

## Dry Moly

Breathing high levels of toluene during pregnancy has been shown to result in children with birth defects and to retard mental abilities and growth.

**CARCINOGENICITY:** OSHA: No ACGIH: No NTP: No IARC: 3 - Not classifiable **OTHER:** CA Prop 65

### SECTION XII – ECOLOGICAL INFORMATION

**ECOTOXICITY:** Avoid release to the environment. **Acetone** (67-64-1): LC<sub>50</sub> (*Oncorhynchus mykiss*, 96h) 5540 mg/L; EC<sub>50</sub> (*Daphnia magna*, 48h) 6100 mg/L; EC<sub>50</sub> (*Selenastrum quadricauda*, 8d) 7500 mg/L; EC<sub>50</sub> (*Psuedomonas putida*, 16h) 1700 mg/L. **Toluene** (108-88-3): LC<sub>50</sub> (*Oncorhynchus mykiss*, 96h) 5.8 mg/L; LC<sub>50</sub> (*Pimephales promelas*) 12.6 mg/L; EC<sub>50</sub> (*Daphnia magna*, 48h) 6 mg/L; EC<sub>50</sub> (*Pseudokirchneriella subcapitata*, 72h) 12 mg/L; EC<sub>50</sub> (*Photobacterium phosphoreum*, 30m) 20 mg/L. **PERSISTENCE AND DEGRADABILITY:** Component or components of this product are expected to biodegrade over time. **BIOACCUMULATIVE POTENTIAL:** Component or components in this product are not expected to bioaccumulate. **MOBILITY IN SOIL:** This product is mobile in soil. **OTHER ADVERSE EFFECTS:** None known.

### SECTION XIII – DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL:** Dispose of in accordance with local, state and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container. **RCRA STATUS:** Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

### SECTION XIV - TRANSPORT INFORMATION

**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.  
**HAZARD CLASS/DIVISION:** 2.1  
**UN/NA NUMBER:** UN1950  
**PACKING GROUP:** N/A

#### AIR SHIPMENT

**PROPER SHIPPING NAME:** Aerosols, flammable.  
**HAZARD CLASS/DIVISION:** 2.1  
**UN/NA NUMBER:** UN1950  
**PACKING GROUP:** N/A

#### SHIPPING BY WATER:

**VESSEL (IMO/IMDG)**  
**PROPER SHIPPING NAME:** Aerosols.  
**HAZARD CLASS/DIVISION:** 2.1  
**UN/NA NUMBER:** UN1950  
**PACKING GROUP:** N/A  
**ENVIRONMENTAL HAZARDS WATER:** Marine Pollutant.

### SECTION XV - REGULATORY INFORMATION

**TSCA STATUS:** All chemicals are listed or exempt.  
**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):** **Acetone** (67-64-1) Reportable Quantity = 5,000 pounds. **Toluene** (108-88-3) Reportable Quantity = 1000 pounds.  
**SARA 311/312 HAZARD CATEGORIES:** Flammable (gases, aerosols, liquids, solids). Gas under pressure. Skin corrosion or irritation. Serious eye damage or eye irritation. Reproductive toxicity. Specific target organ toxicity (single or repeated exposure). Aspiration hazard.  
**SARA 313 REPORTABLE INGREDIENTS:** **Toluene** (108-88-3).  
**CLEAN WATER ACT:** **Acetone** (67-64-1) is a hazardous substance. **Toluene** (108-88-3) is a hazardous substance, a priority pollutant and a toxic pollutant.  
**STATE REGULATIONS: California Proposition 65: WARNING:** This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). **Acetone** (67-64-1): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, DE, ID, ME, MA, MN, NJ, PA, RI, WA. **Toluene** (108-88-3): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, DE, ID, IL, ME, MA, MI, MN, NJ, NY, NC, PA, RI, WA, WI. **Propane** (74-98-6): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CT, DE, MA, MN, NJ, PA.

# Safety Data Sheet

## Dry Moly

**INTERNATIONAL REGULATIONS:** Listed or exempt from listing/notification on the following chemical inventories: Australian Inventory of Industrial Chemicals (AIIC, Australia); Domestic Substances List (DSL, Canada); Inventory of Existing Chemical Substances in China (IECSC, China); Korean Existing Chemicals Inventory (KECI, Korea); New Zealand Inventory of Chemicals (NZIoC, New Zealand; Philippine Inventory of Chemicals and Chemical Substances (PICCS, Philippines).

**VOLATILE ORGANIC COMPOUNDS (VOC):** 60%

**NFPA HEALTH:** 2  
**NFPA FLAMMABILITY:** 3  
**NFPA REACTIVITY:** 0  
**NFPA OTHER:** None

**HMIS HEALTH:** \*2  
**HMIS FLAMMABILITY:** 3  
**HMIS REACTIVITY:** 0  
**HMIS PROTECTION:** C

### SECTION XVI - OTHER INFORMATION

**PREPARATION BY:** Craig Bernard

**DATE PREPARED:** 09/09/2024

**REVISION DATE:** N/A

N/A = Not Applicable; N/D = Not Determined

**DISCLAIMER:** To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.