

GEAR OILS

MOTOR OILS

HYDRAULIC OILS

PIPE COATINGS

THREAD SEALANTS

BEARING GREASES

SPECIALTY

GREASES

THREAD

COMPOUNDS

SUCKER ROD

COATINGS

OUTSIDE **PRESERVATIVES**

WIRELINE

GREASE SEALS

CLEANERS &

DEGREASERS

PIPE STORAGE

COMPOUNDS

THREAD LOCKING COMPOUNDS

> **LUBRICANTS & SEALANTS**

TOOL JOINT & DRILL COLLAR

RUST & CORROSION **INHIBITORS**

VALVE

Liquid-O-Ring®*

YOUR SUPER CENTER FOR OVER 1,000 TOP PERFORMANCE PRODUCTS SERVING INDUSTRIES WORLDWIDE

W.OILCENTER.COM

PROTEKTO-COAT®

922

BLACK EXTERNAL PIPE COATING

PRODUCT DESCRIPTION

Protekto-Coat® 922 is a black, asphalt-based external coating formulated to provide an excellent long-term protective coating to external tubular surfaces while the pipe is in storage. Protekto-Coat® 922 provides economical protection against rust and corrosion. Recommended for tubing, casing, drill collars, and line pipe, Protekto-Coat® 922 dries to a tough, durable film that seals the surface from air, moisture, and the elements.

Protekto-Coat® 922 applications include drill pipe, wash pipe, pump columns, work strings or other applications where medium term protection is required.

BENEFITS

- Economical
- No visible pipe imperfections
- Humidity and salt resistant
- Prevents rusting

TYPICAL OBSERVATIONS

Type	Asphaltic
Color	Black
Odor	Mild Hydrocarbon
Viscosity, #4 cup @ 77°F (25°C)	15-17 sec
Density, lb/gal @ 77°F (25°C)	7.00
Specific Gravity, @ 77°F (25°C)	0.839
Drying Time, ASTM D-5895	10–15 min
Flash Point, ASTM D-93	105°F (40.5°C)
VOC, lb/gal	3.89
Shelf Life (unopened container)	One year

RELATED PRODUCTS

912 External Pipe Coating (Clear, Glossy) 923 External Pipe Coating (Amber, Glossy)

- Excellent adhesion with only minimal surface preparation



based on their specific application.

© 2012, BALMAR LLC Made in U.S.A.

application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise.

ach user should independently determine the suitability of this product

WARRANTY Because the conditions of use and the supervision of

BALMAR LLC 616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507

Manufactured by

The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our web site, www.oilcenter.com, or contact your Account Representative for the most

01/11/13

*Registered trade name of

Oil Center Research, Inc.

Sales Locations:

LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK current information relating to this product.