

LAYOUT DYE REMOVER

SP606



Features EZ-Touch® comfort nozzle

HMIS Hazard Rating: Health (2) • Flammability (3) • Reactivity (0)

- Fast acting formula
- Leaves no residue
- No chlorinated solvents
- Removes old inks, oil, greases



PRESERVE. PROTECT. PREVENT.™

Sprayon® SP™606 Layout Dye Remover is specially formulated to remove Sprayon® SP™603 Blue Layout Dye or other layout fluids quickly and efficiently. It may also be used to remove light oils, greases, many different types of paint and other markings on metal or glass. Eliminates the use of daubers, and brushes. Does not contain methylene chloride.

USES

 Removes inks, oils and paints

SPECIALTY PRODUCTS

APPLICATION

Surface must be free of grease, dirt, and oil. Use in a well ventilated area. Shake can until ball rattles for 1 minute. Hold container upright 8-10" from the surface. Do not apply in continuous spray. To avoid runs, apply several thins coats allowing paint film to become tacky between coats. For best results, use at room temperature (70°F.) After spraying, turn can upside down and spray until clear propellant comes out.

PERFORMANCE

- Non Chlorinated
- NOTE: May be harmful to plastics
- Eliminates brushing
- Equipped with EZ TOUCH® Standard Nozzle
- SHELF LIFE: 3 years from date of manufacture

PROPERTIES

SOLVENT: Hydrocarbon solvent blend

APPEARANCE: Clear ODOR: Solvent

PROPELLANT: Propane

WT./GAL.: 6.63

SPECIFIC GRAVITY: 0.80 HAZARD CODE: 2,3,0

VOC: 93.00%

OTC & CALIFORNIA COMPLIANT: Yes

FLAMMABLE: Yes FLASH POINT: < 0°F



MSDS/EDS/PRODUCT DATA SHEETS: sprayon.com CUSTOMER SERVICE: 1-800-777-2966 TECHNICAL INFORMATION: 1-800-251-2486

PACKAGING

Stock #: S00606 UPC Code: 0-75577-90606-2

Fill Wt.: 12.75 oz.
Per Case: 12
Carton Dimensions:
L 10-7/8" x W 8-3/16" x H 8"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.





© 2010 Sprayon® Products Made in U.S.A.



Distributed by:



Sprayon® Products

101 Prospect Ave. NW Cleveland, OH 44115 Sprayon.com 1-800-777-2966