

Packaged in 3 oz. Tubes Only

KOLOR KUT WATER FINDING PASTE is golden brown in color and turns brilliant red upon contact with water. This product will successfully gauge water content in all petroleum and hydrocarbons as well as sulfuric acid, nitric acid, hydrochloric acid, ammonia, soap solutions, salt and other chloride solutions.

DIRECTIONS FOR USE Place a thin film of KOLOR KUT WATER FINDING PASTE

on a clean gauge line or rod approximately where water level is expected to appear. Lower tape into tank until bottom is reached. Level will appear by positive contrast of colors. Instantaneous in gasoline, diesel, kerosene and gas oils. Heavy oils require a few seconds.



Packaged in 2.25 oz. Plastic Jars Only

KOLOR KUT GASOLINE

GAUGING PASTE is light pink

in color and turns red upon

naphtha, kerosene, gas oil,

hydrocarbons. A most

effective product level

indicator.

contact with gasoline, diesel,

crude oil, jet fuels, and other

61 61 60 59 AFTER GAUGING FOR 56 66 55 66 56 66 55 66 55 66 55 66 55 66 55 66 55 56 55 56 55 56 56 56 55 56 57 56 58 56 59 56 50 56



 \bigcirc

 \bigcirc

Store at temperature range of 35° F to 115° F for preservation of product.

VATER FINDING PASTE



Packaged in 2.5 oz. Tubes Only

Conforms to MIL-W-83779

KOLOR KUT MODIFIED WATER FINDING PASTE has

been designed for use in Methanol, Ethanol enriched fuel systems. Alcohols are soluble in fuels in all proportions when they are water-free but relatively small amounts of water can cause separation of alcohol from the fuel. The mixture settling to the bottom of the storage tank contains a high concentration of alcohol and cannot be detected by most water detection pastes.

KOLOR KUT MODIFIED WATER FINDING PASTE

-15

-14

13

ALCOHOL/WATER BOTTOM

WATER BOTTOM

changes from dark brown in color to bright red on contact with water. Phase separated alcohol solutions with as little as 6% water will turn the paste yellow. This product is designed for use in **reformulated and oxygenated** fuel systems. After testing, it

fuel systems. After testing, it seems that alcohol or deicing agents in fuels have very little effect on the performance of the product.



-16

П

X

GAUGING FOR WATER

FORE

GAUGING FOR WATER