

DRILLING COMPOUND

BESTOLIFE® PB BLACK



3 1/2 Gallon Metal Pail

PRODUCT CHARACTERISTICS

| | |
|--|---|
| Color: | Black |
| Penetration: (ASTM D217) | 290-310 |
| NLGI Grade: | 1.5 |
| Weight/Gallon: | 18.3 pounds/gallon |
| Thickener: | Lithium |
| Fluid Type: | Petroleum |
| Dropping Point: (ASTM D2265) | ≥350°F (≥177°C) |
| Flash Point: | ≥392°F (≥200°C) |
| Brushable To: | 10°F (-12°C) |
| Service Rating: | 500°F (260°C) |
| Friction Factor: | 1.0* |
| Shelf Life: (Unopened container) | 4 years |
| Contains: | Metallic lead and other nonmetallic additives |

*NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

DESCRIPTION

BESTOLIFE® PB Black is an economical lead-based compound for use on drill collars, drill pipe, and other threaded connections. It performs comparably to more expensive drill collar compounds at a very competitive cost.

APPLICATIONS

Economical drill collar compound.

TECHNICAL DATA

BESTOLIFE® PB Black is an economical lead base compound designed for use on drill collars, drill pipe, and other threaded connections. It will provide performance comparable to other more expensive drill collar compounds at a very competitive cost. BESTOLIFE® PB Black contains pure metallic lead blended with other non metallic additives in a high-quality base grease, and is not affected by H₂S or drilling fluids.

NOTES

BESTOLIFE® PB Black meets all applicable API and IADC standards.

PACKAGING

| PRODUCT NUMBER | CONTAINER SIZE | CONTAINER WEIGHT |
|----------------|----------------|------------------|
| 600750 | 3 1/2 gallon | 50 pounds metal |

Note: All package sizes are not listed. Call your sales representative for a complete listing.

