



Super White™ Multi-Purpose Lithium Grease, 10 Wt Oz No. SL3360 | Item# 1007916 | Case# 1007915

Product Description

A high purity, NLGI Grade 2 multi-purpose white lithium grease. Provides superior lubrication & durability in any weather and most temperatures. Bright white in color. Ideal for when appearance is important.

Applications

Assembly lubes, bearings, break-in lubrication for bearings, cables, chains, chassis points, conveyor bearings, door tracks, garage door channels & openers, hinges, latches, machinery, open gears, overhead door tracks, roller bearings, sleeve bearings.

Unit Package Description

10 Ounce Tube

Brand

Sta-Lube

Generic Description 1

Super White Multi-Purpose Grease

Net Fill

10 Wt Oz

UPC Code

072213336009

Unit Dimensions

10H x 3W x 2D in

Units Per Case

6

Case Dimensions

4.13H x 6.75W x 10.25D in

Cases Per Pallet

250

Case Weight

5 lbs

I 2 of 5 Code

30072213336000

Appearance

White Semi-Solid to Solid Grease

Base Type

Lithium-12

Flash point (F)

475°F

Flash point (C)

246°C

Flammability Class - CPSC

None

Spec Gravity Concentrate

0.9 at 60°F

NLGI Grade

2

Timken OK Load Lbs.

25 Lbs

Plastic Safe

Not Determined

Evaporation Rate

<0.01 (Butyl Acetate=1)

Last revised: 7/30/2019

Page 1 of 2



Chemical Solutions to Keep You Moving™
f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



| | |
|---------------------------------|---|
| Working Temp (F) | 0 to 300°F |
| Working Temp (C) | -17.8 to 148.9°C |
| Drop Point | 350°F |
| Leakage | 5 |
| Oil Separation | 5 |
| Oxidation Stability | 10 |
| Pour Point (F) | 0°F |
| Pour Point (C) | -17.78°C |
| ISO Viscosity Grade | 165 |
| Water Washout | 10 |
| Worked Penetration | 285 to 295 |
| Propellant | None |
| NSF Category Code | H2 |
| NSF Number | 147593 |
| DOT Proper Shipping Name | Not Regulated |
| VOC % (Consumer Product def) | <0.1 |
| VOC g/L (Consumer Product def) | <0.9 |
| VOC lbs/gal (Consumer Prod def) | <0.01 |
| VOC Category | Not Regulated |
| Removal (How To) | Remove with a degreaser or brake cleaner product. |

Last revised: 7/30/2019
Page 2 of 2



Chemical Solutions to Keep You Moving™
f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.