



Dry Graphite Lube, 10 Wt Oz

No. 03094 | Item# 1003362 | Case# 1003361

Product Description Ideal where a dry lubricant is required or where petroleum

products must be avoided. Resists dirt, dust and oil buildup. Wide effective temperature range up to 850°F

constant.

Applications Gaskets, transfer belts, conveyor belts, motors, plant

machinery and handling equipment, rubber moldings, high temperature, low load, or high rpm slides, rollers, wheels,

gears, chains & hoists

Unit Package Description 16 Ounce Aerosol

Brand CRC

Generic Description 1 Dry Graphite Lube

Net Fill 10 Wt Oz

UPC Code 078254030944

Unit Dimensions 7.75H x 2.63W x 2.63D in

Units Per Case 12

Case Dimensions 8.69H x 8.44W x 11.31D in

Cases Per Pallet 133
Case Weight 12 lbs

1 2 of 5 Code 30078254030945

Appearance Black Liquid
Flash point (F) -20.2°F
Flash point (C) -29°C

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.66
Plastic Safe Yes
Film Type Dry

Evaporation Rate Moderate

Working Temp (F) 850°F (Constant) / 1000°F (Intermittent)
Working Temp (C) 454.4°C (Constant) 537.8°C (Intermittent)

Propellant Hydrocarbon

Last revised: 9/5/2019

Page 1 of 2







Aerosol Flammability Level III

DOT Proper Shipping Name Aerosols, Flammable, Limited Quantity (Marine Pollutant)

VOC % (Consumer Product 98.8

def)

VOC g/L (Consumer 652.1

Product def)

VOC lbs/gal (Consumer 5.43

Prod def)

VOC Category Dry Film Lubricant

Removal (How To) Remove with petroleum solvents.

Last revised: 9/5/2019

Page 2 of 2

