



Electrical Silicone Lubricant, 55 Gal No. 02097 | Item# 1003203

Product Description Specially formulated to lubricate, waterproof and protect

electrical components. Meets FDA Regulation CFR 21-178.3570 for incidental food contact. NSF H1 Registered.

Applications Helps prevent corrosion to electrical equipment located in

wet or harsh environments.

Unit Package Description 55 Gallon Drum

Brand CRC

Generic Description 1 Dry Film Silicone Lubricant

Net Fill 55 Gal

UPC Code 078254020976

Unit Dimensions 35H x 24.5W x 24.5D in

Units Per Case 1

Case Dimensions 35H x 24.5W x 24.5D in

Cases Per Pallet 4

Case Weight 346 lbs

Appearance Clear Water-White Liquid

Base Type Silicone Flash point (F) $<0^{\circ}F$ Flash point (C) $<-18^{\circ}C$

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.6694

Plastic Safe May Harm Sensitive Plastics
Film Type Dry, Clear, Non-Hardening

Evaporation Rate Fast

Dielectric Strength 350 Volts/Mil
Working Temp (F) -40 to 400°F
Working Temp (C) -40 to 204.4°C

Propellant None
NSF Category Code H1

Last revised: 9/5/2019

Page 1 of 2







NSF Number 111206

DOT Proper Shipping Name Hexane Mixture (Marine Pollutant)

VOC % (Consumer Product 97

def)

VOC g/L (Consumer 649.3

Product def)

VOC lbs/gal (Consumer 5.4

Prod def)

VOC Category Not Regulated (Single Purpose Lubricant)

Removal (How To) Remove with soap & water, CRC HydroForce® All

Purpose, etc. and elbow power (scrubbing).

