



Hi Temperature Disc Brake Wheel Bearing Grease, 14 Wt Oz

No. SL3161 | Item# 1007881 | Case# 1007880

Product Description

A very stable resistant Aluminum Complex grease. Contains rust & oxidation inhibitors, anti-wear and extreme pressure additives & fortified with "moly" and graphite. For use in automotive disc/drum brakes, chassis and suspension systems

Applications

Automotive applications, ball joints, bearings, chassis points, construction ball & roller bearings, conveyor bearings, disc-brake systems, farm equipment, guides, mining applications, press rolls, roller bearings, slides, wheel bearings

Unit Package Description

14 Ounce Can

Brand

Sta-Lube

Generic Description 1

Hi-Temp Disc Brake Wheel Grease

Net Fill

14 Wt Oz

UPC Code

072213316100

Unit Dimensions

3.44H x 4.13W x 4.13D in

Units Per Case

12

Case Dimensions

3.5H x 12.5W x 17D in

Cases Per Pallet

108

Case Weight

13 lbs

I 2 of 5 Code

30072213316101

Appearance

Dark Gray Semi-Solid to Solid Grease

Base Type

Aluminum Complex

Flash point (F)

>450°F

Flash point (C)

>232°C

Flammability Class - CPSC

None

Spec Gravity Concentrate

0.9 at 60°F

NLGI Grade

2

Timken OK Load Lbs.

60 Lbs

Plastic Safe

Not Determined

Evaporation Rate

<0.01 (Butyl Acetate=1)

Last revised: 4/23/2019

Page 1 of 2



Chemical Solutions to Keep You Moving™
f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



Working Temp (F)	0 to 325°F
Working Temp (C)	-18 to 162.5°C
4 Ball EP	30 LWI, 315 Kg Weld
4 Ball Wear	0.75 mm
Drop Point	500°F
Elastomer Compatibility	0 to 30% vol; 0 to 15 hard
Leakage	10g Max
Oil Separation	<10%
Oxidation Stability	2 to 3
Pour Point (F)	0°F
Pour Point (C)	-17.78°C
ISO Viscosity Grade	205
Water Washout	<15%
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0.4
VOC g/L (Consumer Product def)	3.6
VOC lbs/gal (Consumer Prod def)	0.03
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

Last revised: 4/23/2019
Page 2 of 2



Chemical Solutions to Keep You Moving™
f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.