



Marine Boat Trailer and 4x4 Wheel Bearing Grease, 14 Wt Oz No. SL3121 | Item# 1007858 | Case# 1007857

Product Description A blue tacky, aluminum complex grease using a highly

refined base oil. It has been formulated with a polymer to

provide adhesive, non-blend and water wash-out characteristics. Will resist water under the most severe

water conditions.

Applications Anti-friction bearings, blocks, boat trailer bearings, deck

equipment, marine equipment, shaft log seals, sleeve bearings, slides, steering cables, steering dockside machinery, steering quadrants, turnbuckles, wheel

bearings, winches

Unit Package Description 14 Ounce Can

Brand Sta-Lube

Generic Description 1 Marine Grease for Boat Trailer

Net Fill 14 Wt Oz

UPC Code 072213312102

Unit Dimensions 3.44H x 4.13W x 4.13D in

Units Per Case 12

Case Dimensions 3.5H x 12.5W x 17D in

Cases Per Pallet 108
Case Weight 13 lbs

I 2 of 5 Code 30072213312103

Appearance Blue Semi-Solid to Solid Grease

Base Type Aluminum Complex

Flash point (F)  $>450^{\circ}F$ Flash point (C)  $>232.2^{\circ}C$ 

Flammability Class - CPSC None
Spec Gravity Concentrate 0.9
NLGI Grade 2

Plastic Safe Not Determined

Evaporation Rate Slow

Working Temp (F) 0 to 325°F

Last revised: 1/16/2019

Page 1 of 2







Working Temp (C) -17.8 to 162°C

Drop Point 500°F

Leakage 5

Oxidation Stability 5

Pour Point (F) 0°F

Pour Point (C) -17.78°C

ISO Viscosity Grade 180 Cst at 40°C

Water Washout 5% at 175°F

Worked Penetration 265 to 295

Propellant None

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product )

def)

VOC g/L (Consumer 0

Product def)

VOC lbs/gal (Consumer 0

Prod def)

VOC Category Not Regulated

Removal (How To) Remove with a degreaser or brake cleaner product.

Last revised: 1/16/2019

Page 2 of 2

