

SAFETY DATA SHEET

1. Identification

Product identifier	Minute Mend™ Epoxy Putty		
Other means of identification			
Product Code	No. 14070 (Item# 1004796)		
Recommended use	Permanent repair of holes and gouges		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/	Distributor information		
Manufactured or sold by:			
Company name	CRC Industries, Inc.		
Address	885 Louis Dr.		
	Warminster, PA 18974 US		
Telephone			
General Information	215-674-4300		
Technical Assistance	800-521-3168		
Customer Service	800-272-4620		
24-Hour Emergency	800-424-9300 (US)		
(CHEMTREC) Website	703-527-3887 (International) www.crcindustries.com		
	www.cicindustnes.com		
2. Hazard(s) identification			
Physical hazards	Not classified.		
Health hazards	Sensitization, skin	Category 1	
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3	
	Hazardous to the aquatic environment, long-term hazard	Category 3	
OSHA defined hazards	Not classified.		
Label elements			
Signal word	Warning		
Hazard statement	May cause an allergic skin reaction. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.		
Precautionary statement			
Prevention	Avoid breathing vapors. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves.		
Response	If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.		
Storage	Store away from incompatible materials.		
Disposal	Dispose of contents/container in accordance v	Dispose of contents/container in accordance with local/regional/national regulations.	
Hazard(s) not otherwise classified (HNOC)	None known.		
Supplemental information	None.		

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
talc (not containing asbestos fibers)		14807-96-6	40 - 50
glass, oxide, chemicals		65997-17-3	20 - 30
bisphenol A, epichlorohydrin polymer		25068-38-6	5 - 10
titanium dioxide		13463-67-7	5 - 10
3,6-diazaoctanethylenediamin		112-24-3	< 1
quartz		14808-60-7	< 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, trained personnel should give oxygen. Do not use mouth-to-mouth method if victim inhaled the substance. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.
Most important symptoms/effects, acute and delayed	Irritation of eyes and mucous membranes. Rash. May cause an allergic skin reaction. Dermatitis.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation.		
Methods and materials for containment and cleaning up	Sweep up or vacuum up spillage and collect in suitable container for disposal. Following product recovery, flush area with water. Prevent entry into waterways, sewer, basements or confined areas.		
Environmental precautions	Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination.		
7. Handling and storage			
Precautions for safe handling	Avoid breathing vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. When using, do not eat, drink or smoke. Wash hands after handling and before eating. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.		
Conditions for safe storage, including any incompatibilities	Store in original tightly closed container. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Do not store container above 95 °F/35 °C.		

8. Exposure controls/personal protection

Components	Туре	Value	Form
quartz (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CF	R 1910,1000)		
Components	Туре	Value	Form
quartz (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
talc (not containing asbestos fibers) (CAS 14807-96-6)	TWA	0.1 mg/m3	Respirable.
,		20 mppcf	
		2.4 mppcf	Respirable.
titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Components	: Values Type	Value	Form
 guartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
talc (not containing asbestos fibers) (CAS	TWA	2 mg/m3	Respirable fraction.
14807-96-6) titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to			-
Components	Туре	Value	Form
glass, oxide, chemicals (CAS 65997-17-3)	TWA	3 fibers/cm3	Fiber.
		3 fibers/cm3	Fibrous dust.
		5 mg/m3	fibers, total dust
		5 mg/m3	Fiber, total
quartz (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
talc (not containing asbestos fibers) (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.
	ital Exposure Level (WEEL) Guides		
Components	Туре	Value	
3,6-diazaoctanethylenedia min (CAS 112-24-3)	TWA	6 mg/m3	
		1 ppm	
ogical limit values	No biological exposure limits noted for the ing		
osure guidelines	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.		
US WEEL Guides: Skin des	ignation		
3,6-diazaoctanethylened	iamin (CAS 112-24-3) Can be absor	rbed through the skin.	
	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. I exposure limits have not been established, maintain airborne levels to an acceptable level.		
	or other engineering controls to maintain airb	orne levels below recon	nmended exposure limits
propriate engineering trols vidual protection measures	or other engineering controls to maintain airb	orne levels below recon	nmended exposure limits

Skin protection Hand protection	Wear protective gloves such as: Rubber.
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	None required for normal work where adequate ventilation is provided. Respiratory protection should be worn if material is to be sanded or sawed to avoid inhalation of airborne particles. In this situation, a cartridge respirator with an organic vapor cartridge and a P100 filter should be used. Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance				
Physical state	Solid.			
Form	Semi-solid paste.			
Color	Green. White.			
Odor	Pungent. Sulphurous.			
Odor threshold	Not available.			
рН	Not available.			
Melting point/freezing point	Not available.			
Initial boiling point and boiling range	> 392 °F (> 200 °C)			
Flash point	> 200 °F (> 93.3 °C) Setaflash			
Evaporation rate	Not available.			
Flammability (solid, gas)	Not available.			
Upper/lower flammability or exp	plosive limits			
Flammability limit - lower (%)	Not available.			
Flammability limit - upper (%)	Not available.			
Vapor pressure	406.9 hPa estimated			
Vapor density	Not available.			
Relative density	1.97			
Solubility(ies)				
Solubility (water)	Insoluble.			
Partition coefficient (n-octanol/water)	Not available.			
Auto-ignition temperature	Not available.			
Decomposition temperature	> 392 °F (> 200 °C)			
Percent volatile	0 %			

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Temperatures above 35 °C. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides. Nitrogen oxides (NOx). Sulfur oxides. Metal oxides. Halogenated materials.

11. Toxicological information

Information on likely routes of exposure Inhalation Prolonged inhalation may be harmful. Skin contact May cause an allergic skin reaction. Eye contact Direct contact with eyes may cause temporary irritation. Expected to be a low ingestion hazard. Ingestion Symptoms related to the May cause an allergic skin reaction. Dermatitis. Rash. physical, chemical and toxicological characteristics Information on toxicological effects Not known. Acute toxicity Components **Species Test Results** bisphenol A, epichlorohydrin polymer (CAS 25068-38-6) Acute Oral LD50 Rat 11400 mg/kg quartz (CAS 14808-60-7) Acute Oral LD50 Rat 500 mg/kg titanium dioxide (CAS 13463-67-7) Acute Dermal LD50 Rabbit > 10000 mg/kg Oral LD50 Rat > 10000 mg/kg Prolonged skin contact may cause temporary irritation. Skin corrosion/irritation Direct contact with eyes may cause temporary irritation. Serious eye damage/eye irritation Respiratory or skin sensitization **Respiratory sensitization** Not a respiratory sensitizer. Skin sensitization May cause an allergic skin reaction. Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. Carcinogenicity Not classifiable as to carcinogenicity to humans. IARC Monographs. Overall Evaluation of Carcinogenicity Not listed. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052) Not regulated. US. National Toxicology Program (NTP) Report on Carcinogens Not listed. This product is not expected to cause reproductive or developmental effects. Reproductive toxicity Specific target organ toxicity -Not classified. single exposure Specific target organ toxicity -Not classified. repeated exposure Aspiration hazard Not an aspiration hazard. **Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Components		Species	Test Results	
bisphenol A, epichlorohydrin	polymer (CA	AS 25068-38-6)		
Aquatic				
Acute				
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	3.6 mg/l, 96 hours	
titanium dioxide (CAS 13463	-67-7)			
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours	
Acute				
Fish	LC50	Fathead minnow (Pimephales promelas)	1000 mg/l, 96 hours	
rsistence and degradability	No data i	No data is available on the degradability of any ingredients in the mixture.		
oaccumulative potential				
Bioconcentration factor (B titanium dioxide	CF)	352		
obility in soil	No data a	No data available.		
her adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.			
3. Disposal consideration	ons			
zardous waste code	Not regul	Not regulated.		
ontaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.			

	Since emptied containers may retain product residue, follow label warnings even after container is emptied.
Disposal instructions	This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regu	lations	
		n 112 Hazardous Air Pollutants (HAPs) List
Not regula Clean Air Act Not regula	CAA) Section	n 112(r) Accidental Release Prevention (40 CFR 68.130)
Safe Drinking (SDWA)	Water Act	Not regulated.
Food and Drug Administration		Not regulated.
Superfund Amend	ments and Re	eauthorization Act of 1986 (SARA)
Classified categories		Acute toxicity (any route of exposure) Respiratory or skin sensitization
SARA 302 Ext Not listed.	remely hazaro	dous substance
SARA 313 (TR Not regula		
US state regulation	าร	
US. New Jerse	y Worker and	d Community Right-to-Know Act
glass, oxid quartz (CA	e, chemicals ((S 14808-60-7)	iamin (CAS 112-24-3) CAS 65997-17-3)) stos fibers) (CAS 14807-96-6)
	oxide (CAS 13	3463-67-7)
glass, oxid quartz (CA talc (not co	e, chemicals (S 14808-60-7) ntaining asbes	stos fibers) (CAS 14807-96-6)
	oxide (CAS 13 nia Worker a	nd Community Right-to-Know Law
-		iamin (CAS 112-24-3)
glass, oxid quartz (CA	e, chemicals ((S 14808-60-7)	CAS 65997-17-3)
titanium die US. Rhode Isla	oxide (CAS 13 Ind RTK	3463-67-7)
		CAS 65997-17-3)
talc (not co	S 14808-60-7) Intaining asbes Dxide (CAS 13	stos fibers) (CAS 14807-96-6)
California	Proposition 6	65
	WARNING:	: Reproductive Harm - www.P65Warnings.ca.gov
California	Proposition 6	65 - CRT: Listed date/Developmental toxin
	nol (CAS 67-5 Proposition 6	56-1) Listed: March 16, 2012 65 - CRT: Listed date/Female reproductive toxin
•	enol A (CAS 80 rnia. Candida	D-05-7) Listed: May 11, 2015 ate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3,
quartz talc (n	(CAS 14808-6 ot containing a	cals (CAS 65997-17-3) 60-7) asbestos fibers) (CAS 14807-96-6) IS 13463-67-7)
Volatile organic co EPA	mpounds (VC	OC) regulations
	ent (40 CFR	0 %

Consumer products Not regulated (40 CFR 59, Subpt. C) State **Consumer products** This product is regulated as a Sealant and Caulking Compound (chemically curing, non-aerosol). This product is compliant for use in all 50 states. 0 % VOC content (CA) VOC content (OTC) 0 % International Inventories Country(s) or region Inventory name On inventory (yes/no)* Australia Australian Inventory of Chemical Substances (AICS) Yes Canada Domestic Substances List (DSL) Yes Canada Non-Domestic Substances List (NDSL) No China Inventory of Existing Chemical Substances in China (IECSC) Yes Europe European Inventory of Existing Commercial Chemical No Substances (EINECS) Europe European List of Notified Chemical Substances (ELINCS) No Inventory of Existing and New Chemical Substances (ENCS) Japan No Existing Chemicals List (ECL) Korea Yes New Zealand New Zealand Inventory Yes Philippines Philippine Inventory of Chemicals and Chemical Substances Yes (PICCS) Taiwan Taiwan Toxic Chemical Substances (TCS) Yes Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	01-26-2015
Revision date	03-08-2018
Prepared by	Allison Yoon
Version #	02
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc
Revision information	This document has undergone significant changes and should be reviewed in its entirety.