



## Power Lube® Industrial High Performance Lubricant w/PTFE, 11 Wt Oz No. 03045 | Item# 1003304 | Case# 1003303

**Product Description** 

POWER LUBE is a high performance, multi-purpose lubricant that utilizes PTFE and extreme pressure additives to provide unparalleled lubricating performance. It has twice the load carrying capacity of most general purpose lubricants.

Bearings, gears, linkages, motors, chains, cables, rollers, guide bars, pulleys, cams, valves, ball joints, hinges, slides, cutting tools, taps, dies, pistons, handling equipment, conveyors, hoists, lifts, doors and fans.

Unit Package Description 16 Ounce Aerosol CRC **Generic Description 1** High Performance Lubricant with PTFE Net Fill 11 Wt Oz **UPC** Code 078254030456 7.75H x 2.63W x 2.63D in Unit Dimensions Units Per Case 12 **Case Dimensions** 8.1H x 8.3W x 11.1D in Cases Per Pallet 133 Case Weight 10 lbs I 2 of 5 Code 30078254030457 Appearance Light Amber Liquid w/white precipitate Petroleum Solvent Base Type Flash point (F) <20°F <-7°C Flash point (C) Flammability Class - CPSC **Extremely Flammable** Spec Gravity Concentrate 0.863 Plastic Safe No Film Type Wet Film Thickness Not Determined

Last revised: 9/5/2019

Page 1 of 2



Chemical Solutions to Keep You Moving... ① ○ ○ ○ ○ ○ ● • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®



## Alto Rendimiento Lubricante C/PTFE

Lubricates Moving Parts Protects Against Corrosion Lubrica Piezas Móviles Protege Contra la Corrosión

RØ

DANGER: EXTREMELY FLAMABLE HARMFUL OR FATAL FONALLOWED, EYE IRRITANT. OVITIONS UNDER PRESSURE. EEP ANAY FROM CHILDREN. We anamops on back panel. PELIGED.

> CAL O MORTAL. TE DE LOS OLOS. DO BAJO PRESIÓN. GA FUERA DEL E DE LOS NIÑOS



**Evaporation Rate** Fast **Dielectric Strength** Not Determined Working Temp (F) Max 300°F Working Temp (C) Max 148.9°C Propellant Hydrocarbon NSF Category Code H2 **NSF** Number 017403 Aerosol Flammability Level Ш DOT Proper Shipping Name Aerosols, Flammable, Limited Quantity VOC % (Consumer Product 23.9 def) 206.3 VOC g/L (Consumer Product def) VOC lbs/gal (Consumer 1.7 Prod def) VOC Category Multi-Purpose Lubricant Removal (How To) Remove with petroleum solvents or mineral spirits.

Last revised: 9/5/2019

Page 2 of 2

CRC

Chemical Solutions to Keep You Moving™ € ♥ ♥ ⊕ ● • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets: CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.