

SAFETY DATA SHEET

1. Identification

Product identifier Sta-Plex™ Extreme Pressure Premium Red Grease

Other means of identification

Product Code No. SL3191 (Item# 1007892)

Recommended use Lubricating grease
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Serious eye damage/eye irritation Category 2A

Sensitization, skin

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary statement

Prevention Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated

work clothing must not be allowed out of the workplace. Wear eye protection/face protection.

Category 1

Wear protective gloves.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation

persists: Get medical advice/attention.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	50 - 70
distillates (petroleum), solvent-dewaxed heavy paraffinic		64742-65-0	15 - 40
calcium carbonate		471-34-1	3 - 7
phosphorodithioic acid, o,o-di-c1-14-alkyl esters, zinc salts		68649-42-3	1 - 5
2-(2-cis-heptadec-8-enyl-2-imidazol n-1-yl)ethanol	i	95-38-5	0.5 - 1.5

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Provide oxygen or artificial respiration if needed. Call a physician if symptoms

develop or persist.

Skin contact Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing

and shoes. In case of eczema or other skin disorders: Seek medical attention and take along

these instructions. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Never give anything by mouth to a victim who is unconscious or is having

convulsions. Do not induce vomiting without advice from poison control center. Get medical

attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Ingestion

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

environment.

Unsuitable extinguishing media

None known.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting Us

equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazardsNo unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

The product is immiscible with water and will spread on the water surface.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

Environmental precautions Avoid discharge into drains, water course

Avoid discharge into drains, water courses or onto the ground. Contact local authorities in case of spillage to drain/aquatic environment.

7. Handling and storage

Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	Form
calcium carbonate (CAS 471-34-1)	PEL	5 mg/m3	Respirable fraction.
·		15 mg/m3	Total dust.
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
US. ACGIH Threshold Limit Val	ues		
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to Cl			_
Components	Туре	Value	Form
calcium carbonate (CAS 471-34-1)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
ogical limit values N	No biological exposure limits noted for the ingredient(s).		

Biological limit values Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Latex gloves. Rubber gloves.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Solid. Grease. **Form** Color Red.

Mild petroleum. Odor **Odor threshold** Not available. Not available. Not available. Melting point/freezing point

Initial boiling point and boiling

range

680 °F (360 °C) estimated

475 °F (246.1 °C) Cleveland Open Cup Flash point

Evaporation rate Slow.

Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits Not available.

Flammability limit - lower

(%)

(%)

Flammability limit - upper

Not available.

Not available. Vapor pressure Vapor density Not available.

0.9 Relative density

Solubility(ies)

Insoluble. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

500 °F (260 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available.

> 21 mm²/s (104 °F (40 °C)) **Viscosity**

Percent volatile Not available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability**

Possibility of hazardous

No dangerous reaction known under conditions of normal use.

Conditions to avoid

reactions

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

Acids. Fluorine. Incompatible materials

Material name: Sta-Plex™ Extreme Pressure Premium Red Grease

SDS US

Carbon oxides. Sulfur oxides. Metal oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful. May cause an allergic skin reaction. Skin contact

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Components **Species Test Results**

calcium carbonate (CAS 471-34-1)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat > 3 mg/l

Oral

LD50 Rat 6450 mg/kg

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

Acute **Dermal**

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat > 5000 mg/kg

distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

Acute **Dermal**

LD50 Rabbit > 5000 mg/kg

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

distillates (petroleum), solvent-dewaxed heavy paraffinic 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-65-0)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Material name: Sta-Plex™ Extreme Pressure Premium Red Grease

SDS US No. SL3191 (Item# 1007892) Version #: 02 Revision date: 11-06-2018 Issue date: 11-06-2018

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

Specific target orga

cicity - Not classified.

repeated exposure

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

phosphorodithioic acid, o,o-di-c1-14-alkyl esters, zinc salts (CAS 68649-42-3)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 1 - 5 mg/l, 48 hours
Fish LC50 Fathead minnow (Pimephales promelas) 1 - 5 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential Mobility in soil No data available.

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty

containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste

disposal site. Dispose in accordance with all applicable regulations.

Hazardous waste code Not regulated.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

phosphorodithioic acid, o,o-di-c1-14-alkyl esters, zinc salts (CAS 68649-42-3)

CERCLA Hazardous Substance List (40 CFR 302.4)

phosphorodithioic acid, o,o-di-c1-14-alkyl esters, zinc Listed.

salts (CAS 68649-42-3)

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Material name: Sta-Plex™ Extreme Pressure Premium Red Grease

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard Acute toxicity (any route of exposure) Serious eye damage or eye irritation categories Respiratory or skin sensitization

SARA 302 Extremely hazardous substance

Not listed.

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
phosphorodithioic acid, o,o-di-c1-14-alkyl esters, zinc salts	68649-42-3	1 - 5

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

calcium carbonate (CAS 471-34-1)

phosphorodithioic acid, o,o-di-c1-14-alkyl esters, zinc salts (CAS 68649-42-3)

US. Massachusetts RTK - Substance List

calcium carbonate (CAS 471-34-1)

US. Pennsylvania Worker and Community Right-to-Know Law

calcium carbonate (CAS 471-34-1)

phosphorodithioic acid, o,o-di-c1-14-alkyl esters, zinc salts (CAS 68649-42-3)

US. Rhode Island RTK

calcium carbonate (CAS 471-34-1)

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR > 65 %

51.100(s))

Consumer products Not regulated

(40 CFR 59, Subpt. C)

State

Not regulated Consumer products < 40 % VOC content (CA) **VOC content (OTC)** < 40 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

Material name: Sta-Plex™ Extreme Pressure Premium Red Grease

SDS US

Country(s) or region Inventory name On inventory (yes/no)*

European Inventory of Existing Commercial Chemical

Substances (EINECS)

New Zealand Inventory

Europe European List of Notified Chemical Substances (ELINCS) No
Japan Inventory of Existing and New Chemical Substances (ENCS) No
Korea Existing Chemicals List (ECL) Yes

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

16. Other information, including date of preparation or last revision

Issue date11-06-2018Revision date11-06-2018Prepared byAllison Yoon

Version # 02

New Zealand

Disclaimer The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Material Hame. Sta-Flex *** Extreme Fressure Fremium Reu Grease

Yes

Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).