



## Syntha-Tech? Lubricant with PTFE, 11 Wt Oz

No. 03054 | Item# 1003310 | Case# 1003309

Product Description NSF, H1 registered, zero VOC, unique blend of synthetic

lubricants that utilizes PTFE, anti-wear and extreme pressure additives to provide unparalleled lubricating

performance.

Applications Bearings, gears, linkages, motors, chains, cables, rollers,

guide bars, pulleys, cams, valves, ball joints, hinges, slides, cutting tools, taps, dies, pistons, handling equipment, conveyors, hoists, lifts, doors, fans, and

processing equipment.

Unit Package Description 16 Ounce Aerosol

Brand CRC

Generic Description 1 Synthetic Lubricant with Perma-Lock®

Net Fill 11 Wt Oz

UPC Code 078254030548

Unit Dimensions 7.75H x 2.63W x 2.63D in

Units Per Case 12

Case Dimensions 8.1H x 8.3W x 11.1D in

Cases Per Pallet 133
Case Weight 12 lbs

I 2 of 5 Code 30078254030549

Appearance White Liquid
Base Type Polyolefin
Flash point (F) 117 F

Flammability Class - CPSC Flammable

Spec Gravity Concentrate 0.8

Flash point (C)

Plastic Safe Safe on Most Plastics (Test small area)

47 C

Film Type Synthetic

Film Thickness Not Determined

Evaporation Rate Slow

Last revised: 1/17/2020

Page 1 of 2







Dielectric Strength 32,480 Volts
Working Temp (F) -40 to 450°F
Working Temp (C) -40 to232.2°C
Propellant Carbon Dioxide

NSF Category Code H1

NSF Number 142820

Aerosol Flammability Level II

DOT Proper Shipping Name Aerosols, flammable

VOC % (Consumer Product 98.1

def)

VOC g/L (Consumer 40.2

Product def)

VOC lbs/gal (Consumer

Prod def)

VOC Category Multi-Purpose Lubricant
Removal (How To) Remove with degreaser

0.34

Last revised: 1/17/2020

Page 2 of 2

