CRO

SAFETY DATA SHEET

1. Identification

Product identifier 3-36® Multi-Purpose Lubricant & Corrosion Inhibitor - 1 pt

Other means of identification

Product Code No. 03007 (Item# 1003259)
Recommended use Multi-purpose lubricant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 4Health hazardsSensitization, skinCategory 1Aspiration hazardCategory 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Combustible liquid. May be fatal if swallowed and enters airways. May cause an allergic skin

reaction.

Precautionary statement

Prevention Keep away from flames and hot surfaces. - No smoking. Use with adequate ventilation. Open

doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist/vapors. Contaminated work clothing must not be allowed out of the

workplace. Wear protective gloves/eye protection/face protection.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash

with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Do not use water jet as an extinguisher, as

this will spread the fire.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

Material name: 3-36® Multi-Purpose Lubricant & Corrosion Inhibitor - 1 pt No. 03007 (Item# 1003259) Version #: 01 Issue date: 03-28-2020

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated light		64742-47-8	60 - 70
distillates (petroleum), hydrotreated heavy paraffinic		64742-54-7	5 - 10
paraffin oils (petroleum), catalytic dewaxed heavy		64742-70-7	5 - 10
paraffin oils (petroleum), catalytic dewaxed light		64742-71-8	5 - 10
butyl stearate		123-95-5	1 - 5
dipropylene glycol methyl ether acetate		88917-22-0	1 - 5
petrolatum		8009-03-8	1 - 5

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special

treatment needed

General information

Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea. Direct contact with eyes may cause temporary irritation. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire-fighting equipment/instructions

Specific methods

General fire hazards

Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Use standard firefighting procedures and consider the hazards of other involved materials.

Use standard firefighting procedures and consider the hazards of other involved materials. Combustible liquid. Will burn if involved in a fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Value

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Type

U.S	OSHA
Comp	onents

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	
US. OSHA Table Z-1 Limits for Air C Components	ontaminants (29 CFR 1910.1000) Type	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	PEL	5 mg/m3	Mist.
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	PEL	5 mg/m3	Mist.
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)	PEL	5 mg/m3	Mist.
petrolatum (CAS 8009-03-8)	PEL	5 mg/m3	Mist.
ACGIH Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction
US. ACGIH Threshold Limit Values Components	Туре	Value	Form
butyl stearate (CAS 123-95-5)	TWA	3 mg/m3	Respirable fraction.
,		10 mg/m3	Inhalable fraction.
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.

Components	Туре	Value	Form
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	TWA	5 mg/m3	Inhalable fraction.
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)	TWA	5 mg/m3	Inhalable fraction.
petrolatum (CAS 8009-03-8)	TWA	5 mg/m3	Inhalable fraction.
U.S NIOSH			_
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist
	TWA	5 mg/m3	Mist
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
,	TWA	5 mg/m3	Mist.
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3	
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
petrolatum (CAS 8009-03-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Biological limit values
Appropriate engineering controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Neoprene. Nitrile.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not

be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Blue green
Odor Pleasant.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

380 °F (193.3 °C) estimated

range

Flash point 192 °F (88.9 °C) Setaflash

Evaporation rate Slow.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

0.5 % estimated

(%)

Flammability limit - upper

5.5 % estimated

(%)

Vapor pressure 0.2 hPa estimated

Vapor density > 1 (air = 1) Relative density 0.83

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 410 °F (210 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

Percent volatile 78.5 % estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides. Sulfur oxides. Hydrogen sulfide. Mercaptans. Sulfides.

11. Toxicological information

Information on likely routes of exposure

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.

Eye contact Based on available data, the classification criteria are not met.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting.

Diarrhea. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components Species Test Results

distillates (petroleum), hydrotreated light (CAS 64742-47-8)

<u>Acute</u>

Dermal

LD50 Rat > 2000 mg/kg

Inhalation

LC50 Rat > 5 mg/l, 4 hours

Oral

LD50 Rat > 5000 mg/kg, 2.5 hours

paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)

<u>Acute</u>

Dermal

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat > 5000 mg/kg

paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)

<u>Acute</u>

Dermal

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

distillates (petroleum), hydrotreated heavy paraffinic

3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-54-7)

paraffin oils (petroleum), catalytic dewaxed light 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-71-8)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)

Aquatic

Acute

Crustacea EC50 Water flea (Daphnia magna) > 10000 mg/l, 48 hours
Fish LC50 Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours

distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 2.9 mg/l, 96 hours

(Oncorhynchus mykiss)

paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)

Aquatic

Acute

Crustacea EC50 Daphnia > 100 mg/l, 48 hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty

containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all

applicable regulations.

Hazardous waste code Not regulated.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard Flammable (gases, aerosols, liquids, or solids)

categories Respiratory or skin sensitization

Aspiration hazard

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

Not listed.

US. Massachusetts RTK - Substance List

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8) petrolatum (CAS 8009-03-8)

US. Pennsylvania Worker and Community Right-to-Know Law

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) distillates (petroleum), hydrotreated light (CAS 64742-47-8) paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8) petrolatum (CAS 8009-03-8)

US. Rhode Island RTK

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) distillates (petroleum), hydrotreated light (CAS 64742-47-8) paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8) petrolatum (CAS 8009-03-8)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) distillates (petroleum), hydrotreated light (CAS 64742-47-8) paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8) petrolatum (CAS 8009-03-8)

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 100 %

51.100(s))

Consumer products Not regulated

(40 CFR 59, Subpt. C)

State

Consumer products This product is regulated as a Multi-Purpose Lubricant. This product is compliant for use in all 50

states.

VOC content (CA) 0 % VOC content (OTC) 0 %

International Inventories

Country(s) or region On inventory (yes/no)* Inventory name Australia Australian Inventory of Chemical Substances (AICS) Canada Domestic Substances List (DSL) Yes Canada Non-Domestic Substances List (NDSL) No China Inventory of Existing Chemical Substances in China (IECSC) Yes European Inventory of Existing Commercial Chemical Europe No Substances (EINECS)

Europe European List of Notified Chemical Substances (ELINCS)

Japan Inventory of Existing and New Chemical Substances (ENCS)

Korea Existing Chemicals List (ECL)

New Zealand Inventory

No

Philippines Philippine Inventory of Chemicals and Chemical Substances No

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

16. Other information, including date of preparation or last revision

Issue date03-28-2020Prepared byAllison Yoon

Version # 01

Further information CRC # 510F/1002511

Disclaimer The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Revision information This document has undergone significant changes and should be reviewed in its entirety.

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).