

COPPER SUPREME SPECIAL BLEND®

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/11/2019

 13.0
 05/06/2020
 115189-00020
 Date of first issue: 05/12/2015

SECTION 1. IDENTIFICATION

Product name : COPPER SUPREME SPECIAL BLEND®

SDS-Identcode : 343G

Manufacturer or supplier's details

Company name of supplier : Bestolife Corporation Address : 2126 Vanco Drive

Irving TX 75061,

Telephone : 855-243-9164/972-865-8961

Telefax : 214-631-3047

Emergency telephone : CHEMTREC U.S.: 800-424-9300, International 703-527-3887

(24-hours/7 days)

E-mail address : www.bestolife.com

Recommended use of the chemical and restrictions on use

Recommended use : Industrial use

Thread Compound (Pipe Dope) and Jacking grease for use in

Offshore industries

Mining, (without offshore industries)

Restrictions on use : Do not use on oxygen lines or in oxygen enriched atmos-

pheres.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Eye irritation : Category 2A

Skin sensitization : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Precautionary Statements : Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.



COPPER SUPREME SPECIAL BLEND®

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/11/2019

 13.0
 05/06/2020
 115189-00020
 Date of first issue: 05/12/2015

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P337 + P313 If eye irritation persists: Get medical advice/ atten-

tion

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated	64742-54-7	>= 30 - < 50
heavy paraffinic		
Distillates (petroleum), hydrotreated	64742-52-5	>= 30 - < 50
heavy naphthenic		
Graphite	7782-42-5	>= 10 - < 20
Copper metal powder	7440-50-8	>= 10 - < 20
Talc	14807-96-6	>= 5 - < 10
Dilithium azelate	38900-29-7	>= 5 - < 10
Dolomite	16389-88-1	>= 1 - < 5
Tris[bis(2-	15991-76-1	>= 1 - < 5
ethylhexyl)dithiocarbamato-S,S']		
antimony		
Calcium oxide	1305-78-8	>= 1 - < 5
Antimony, dialkyl dithiocarbamate	15890-25-2	>= 1 - < 5
Quartz	14808-60-7	>= 1 - < 5
2,5-Bis(octyldithio)-1,3,4-thiadiazole	13539-13-4	>= 0.1 - < 1
	68610-84-4	>= 0.1 - < 1
calcium salts, overbased		

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

Get medical attention.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact In case of contact, immediately flush eyes with plenty of water

Causes serious eye irritation.

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed, DO NOT induce vomiting. If swallowed

Get medical attention if symptoms occur. Rinse mouth thoroughly with water. May cause an allergic skin reaction.

Most important symptoms and effects, both acute and

delayed

Protection of first-aiders

First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Water spray

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Carbon oxides Metal oxides

Nitrogen oxides (NOx)

Sulfur oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice and personal protective

equipment recommendations.

Discharge into the environment must be avoided. Environmental precautions

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for Sweep up or vacuum up spillage and collect in suitable



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

containment and cleaning up container for disposal.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Advice on safe handling Do not get on skin or clothing.

Do not swallow. Do not get in eyes.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Take care to prevent spills, waste and minimize release to the

environment.

Keep in properly labeled containers. Conditions for safe storage

Store in accordance with the particular national regulations.

Materials to avoid Do not store with the following product types:

Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	TWA (Mist)	5 mg/m³	OSHA Z-1
		TWA (Mist)	5 mg/m³	NIOSH REL
		ST (Mist)	10 mg/m³	NIOSH REL
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m³	OSHA Z-1
		TWA (Inhal- able particu- late matter)	5 mg/m³	ACGIH
		TWA (Mist)	5 mg/m³	NIOSH REL
		ST (Mist)	10 mg/m³	NIOSH REL
Graphite	7782-42-5	TWA (Res- pirable)	2.5 mg/m³	NIOSH REL
		TWA (Res- pirable par- ticulate mat- ter)	2 mg/m³	ACGIH
		TWA (Dust)	15 Million particles per cubic foot	OSHA Z-3
Copper metal powder	7440-50-8	TWA (Dust	1 mg/m³	ACGIH



COPPER SUPREME SPECIAL BLEND®

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/11/2019

 13.0
 05/06/2020
 115189-00020
 Date of first issue: 05/12/2015

I		and mist)	(Copper)	1
		TWA	0.2 mg/m ³	ACGIH
		(Fumes)	(Copper)	
		TWA (Dust)	1 mg/m³	NIOSH REL
		, ,	(Copper)	
		TWA (Mist)	1 mg/m³	NIOSH REL
		(,	(Copper)	
		TWA (dusts	1 mg/m³	OSHA Z-1
		and mists)	(Copper)	
		TWA	0.1 mg/m ³	OSHA Z-1
		(Fumes)	(Copper)	
Talc	14807-96-6	TWA (Dust)	20 Million	OSHA Z-3
. 5.15		(2 000)	particles per cubic	00
			foot	
		TWA (Res-	2 mg/m³	NIOSH REL
		pirable)	2 mg/m	MOOTTKEE
		TWA (Res-	2 mg/m³	ACGIH
		pirable par-	2 mg/m	7.00111
		ticulate mat-		
		ter)		
Dolomite	16389-88-1	TWA (Res-	5 mg/m³	NIOSH REL
Bolomite	10000 00 1	pirable)	(Calcium car-	MOOTTKEE
		pirable)	bonate)	
		TWA (total)	10 mg/m³	NIOSH REL
		1 vvv (total)	(Calcium car-	MOOTTKEE
			bonate)	
Tris[bis(2-	15991-76-1	TWA	0.5 mg/m ³	OSHA Z-1
ethylhexyl)dithiocarbamato-	13331-70-1	IVVA	(antimony)	0011A Z-1
S,S'] antimony			(antimorry)	
C,C j driamony		TWA	0.5 mg/m³	ACGIH
		1 447 ((antimony)	7.00111
		TWA	0.5 mg/m ³	NIOSH REL
		1 ***	(antimony)	MOOTTKEE
Calcium oxide	1305-78-8	TWA	2 mg/m³	ACGIH
Calcium Oxide	1000 70 0	TWA	2 mg/m³	NIOSH REL
		TWA	5 mg/m³	OSHA Z-1
Antimony, dialkyl	15890-25-2	TWA	0.5 mg/m³	OSHA Z-1
dithiocarbamate	15090-25-2	IVVA		USHA Z-1
ditillocarbamate		TWA	(antimony) 0.5 mg/m³	ACGIH
		IVVA	(antimony)	ACGIN
		TWA		NIOCH DEL
		IVVA	0.5 mg/m³	NIOSH REL
O and	44000 00 7	TMA /Dee	(antimony)	00114.7.4
Quartz	14808-60-7	TWA (Res-	0.05 mg/m³	OSHA Z-1
		pirable dust)	10 ma/m2	00114.7.0
		TWA (respir-	10 mg/m3	OSHA Z-3
		able)	/ %SiO2+2	00114.7.0
		TWA (respir-	250 mppcf	OSHA Z-3
		able)	/ %SiO2+5	400"
		TWA (Res-	0.025 mg/m³	ACGIH
		pirable par-	(Silica)	1
		ticulate mat-		
		ter)		
		TWA (Res-	0.05 mg/m ³	NIOSH REL
		pirable dust)	(Silica)	



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

PEL (respir-0.05 mg/m3 **OSHA CARC** able)

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Quartz

Minimize workplace exposure concentrations. **Engineering measures**

> Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m3 - total dust, 5 mg/m3 - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m3 - respirable particles, 10 mg/m3 -

inhalable particles.

Personal protective equipment

Respiratory protection General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Chemical-resistant gloves Material

Remarks Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection Wear the following personal protective equipment:

Safety goggles

Skin and body protection Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke.

Wash contaminated clothing before re-use.



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Viscous semi-solid

Color : dark, copper

Odor : Petroleum

Odor Threshold : No data available

pH : Not applicable (not an aqueous solution)

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : $>= 392 \, ^{\circ}\text{F} / >= 200 \, ^{\circ}\text{C}$

Method: ASTM D 92, Cleveland open cup

Distillates (petroleum), hydrotreated heavy naphthenic

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : 1.2

Solubility(ies)

Water solubility : negligible

Partition coefficient: n-

Autoignition temperature

octanol/water

Not applicable

: No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : Not applicable

Flow time : No data available

Explosive properties : Not explosive



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reac- : Can react with strong oxidizing agents.

tions

Conditions to avoid : None known. Incompatible materials : Oxidizing agents

Hazardous decomposition : No hazardous decomposition products are known.

products

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Remarks: Based on data from similar materials

Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials



COPPER SUPREME SPECIAL BLEND®

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/11/2019

 13.0
 05/06/2020
 115189-00020
 Date of first issue: 05/12/2015

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h
Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

Graphite:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 423

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Copper metal powder:

Acute oral toxicity : LD50 (Rat): > 2,500 mg/kg

Method: OECD Test Guideline 423

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 5.11 mg/l

Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Talc:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Remarks: Based on data from similar materials

Dilithium azelate:

Acute oral toxicity : LD50 (Rat): > 300 - 2,000 mg/kg



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

Method: OECD Test Guideline 420

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

Dolomite:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 420

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Remarks: Based on data from similar materials

Calcium oxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 425

Acute inhalation toxicity : (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 436

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg



COPPER SUPREME SPECIAL BLEND®

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/11/2019

 13.0
 05/06/2020
 115189-00020
 Date of first issue: 05/12/2015

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 3.08 mg/l

Exposure time: 4 h
Test atmosphere: dust/mist

Method: OECD Test Guideline 403

: LD50 (Rabbit): > 2,000 mg/kg Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Benzenesulphonic acid, propenated, calcium salts, overbased:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 1.9 mg/l

Exposure time: 4 h
Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

Skin corrosion/irritation

Acute dermal toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit

Result : No skin irritation

Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit

Result : No skin irritation

Remarks : Based on data from similar materials

Graphite:



COPPER SUPREME SPECIAL BLEND®

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/11/2019

 13.0
 05/06/2020
 115189-00020
 Date of first issue: 05/12/2015

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Copper metal powder:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Talc:

Species : Rabbit

Result : No skin irritation

Dilithium azelate:

Method : OECD Test Guideline 439

Result : No skin irritation

Remarks : Based on data from similar materials

Dolomite:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Calcium oxide:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Remarks : Based on data from similar materials

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Benzenesulphonic acid, propenated, calcium salts, overbased:

Species : Rabbit

Result : No skin irritation

Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit

Result : No eye irritation

Remarks : Based on data from similar materials

Graphite:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Copper metal powder:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Talc:

Species : Rabbit

Result : No eye irritation

Dilithium azelate:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Dolomite:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Calcium oxide:

Species : Rabbit

Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Benzenesulphonic acid, propenated, calcium salts, overbased:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Test Type : Buehler Test Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Remarks : Based on data from similar materials

Graphite:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact
Species : Mouse
Result : negative

Copper metal powder:

Test Type : Maximization Test Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Talc:

Routes of exposure : Skin contact Species : Humans Result : negative

Dilithium azelate:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Remarks : Based on data from similar materials



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

Dolomite:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Remarks : Based on data from similar materials

Calcium oxide:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact

Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Remarks : Based on data from similar materials

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Test Type : Buehler Test Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : positive

Assessment : Probability or evidence of high skin sensitization rate in

humans

Benzenesulphonic acid, propenated, calcium salts, overbased:

Test Type : Human repeat insult patch test (HRIPT)

Routes of exposure : Skin contact Result : positive

Remarks : Based on data from similar materials

Assessment : Probability or evidence of skin sensitization in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

Distillates (petroleum), hydrotreated heavy naphthenic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Graphite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Copper metal powder:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Method: Directive 67/548/EEC, Annex V, B.12.

Result: negative

Remarks: Based on data from similar materials

Talc:

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro

Species: Rat

Application Route: Ingestion

Result: negative

Dilithium azelate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

Dolomite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Calcium oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474 Result: equivocal

Result. equivocal

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

Benzenesulphonic acid, propenated, calcium salts, overbased:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Product:

Carcinogenicity - Assess-

ment

: Petroleum distillates have been classified as not carcinogenic

based on DMSO extract content < 3% (Regulation (EC)

1272/2008, Annex VI, Part 3, Note L).

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Mouse
Application Route : Skin contact
Exposure time : 78 weeks

Method : OECD Test Guideline 451

Result : negative

Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Mouse Application Route : Skin contact



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

Exposure time : 78 weeks

Method : OECD Test Guideline 451

Result : negative

Talc:

Species : Mouse

Application Route : inhalation (dust/mist/fume)

Exposure time : 2 Years
Result : negative

Calcium oxide:

Species : Rat
Application Route : Ingestion
Exposure time : 104 weeks
Result : negative

Remarks : Based on data from similar materials

Quartz:

Species : Humans

Application Route : inhalation (dust/mist/fume)

Result : positive

Remarks : These substance(s) are inextricably bound in the product and

therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assess-

ment

: Positive evidence from human epidemiological studies (inhala-

tion)

IARC Group 1: Carcinogenic to humans

Quartz 14808-60-7

(Silica dust, crystalline)

OSHA Specifically regulated carcinogen

Quartz 14808-60-7

(crystalline silica)

NTP Known to be human carcinogen

Quartz 14808-60-7

(Silica, Crystalline (Respirable Size))

Reproductive toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials



COPPER SUPREME SPECIAL BLEND®

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/11/2019

 13.0
 05/06/2020
 115189-00020
 Date of first issue: 05/12/2015

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Skin contact Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

Graphite:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Copper metal powder:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rabbit

Application Route: Ingestion

Result: negative

Talc:

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Dilithium azelate:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Skin contact

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Skin contact



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

Result: negative

Remarks: Based on data from similar materials

Dolomite:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Calcium oxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

Antimony, dialkyl dithiocarbamate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Result: negative

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat



COPPER SUPREME SPECIAL BLEND®

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/11/2019

 13.0
 05/06/2020
 115189-00020
 Date of first issue: 05/12/2015

Application Route: Ingestion

Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Method: OECD Test Guideline 422

Result: negative

Benzenesulphonic acid, propenated, calcium salts, overbased:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 415

Result: negative

Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

Components:

Calcium oxide:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Components:

Quartz:

Routes of exposure : inhalation (dust/mist/fume)

Target Organs : Lungs

Assessment : Shown to produce significant health effects in animals at con-

centrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit

NOAEL : 1,000 mg/kg

Application Route : Skin contact

Exposure time : 4 Weeks

Method : OECD Test Guideline 410

Remarks : Based on data from similar materials

Species : Rat

NOAEL : > 980 mg/m³

Application Route : inhalation (dust/mist/fume)



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

Exposure time : 4 Weeks

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rat

> 0.98 mg/lNOAEL

: inhalation (dust/mist/fume) Application Route

Exposure time : 28 Days

Remarks : Based on data from similar materials

Copper metal powder:

Species : Rat

NOAEL : >= 2 mg/m³

Application Route : inhalation (dust/mist/fume)

Exposure time : 28 Days

Dilithium azelate:

Species : Rat

NOAEL : 1,089.75 mg/kg Application Route : Skin contact Exposure time 28 Days

. Remarks Based on data from similar materials

Dolomite:

Species : Mouse NOAEL 1,300 mg/kg Application Route Ingestion Exposure time 28 Days

Remarks : Based on data from similar materials

Calcium oxide:

Species : Rat

NOAEL : >= 0.399 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 90 Days

Method : OECD Test Guideline 413

Antimony, dialkyl dithiocarbamate:

Species

NOAEL : >= 1,000 mg/kg Application Route : Ingestion Exposure time : 54 Days

Quartz:

Species : Humans LÖAEL : 0.053 mg/m³

: inhalation (dust/mist/fume) Application Route

These substance(s) are inextricably bound in the product and Remarks

therefore do not contribute to a dust inhalation hazard.



COPPER SUPREME SPECIAL BLEND®

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/11/2019

 13.0
 05/06/2020
 115189-00020
 Date of first issue: 05/12/2015

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Species : Rat

NOAEL : 330 mg/kg

Application Route : Ingestion

Exposure time : 54 Days

Method : OECD Test Guideline 422

Benzenesulphonic acid, propenated, calcium salts, overbased:

Species : Rat

NOAEL : > 300 mg/kg
Application Route : Ingestion
Exposure time : 29 Days

Method : OECD Test Guideline 407

Remarks : Based on data from similar materials

Species : Rat

NOAEL : > 600 mg/kg Application Route : Skin contact Exposure time : 28 Days

Method : OECD Test Guideline 410

Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 10,250 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 15,470 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

EC50 (Daphnia magna (Water flea)): 30,940 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): 70,100

mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Selenastrum capricornutum (green algae)): 60,000

mg/l



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

Exposure time: 96 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

olants

EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 10 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

: NOEC: > 1.93 mg/l Toxicity to microorganisms

Exposure time: 10 min Method: DIN 38 412 Part 8

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

olants

: EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mq/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 10 mg/l

Exposure time: 21 d

Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

Exposure time: 10 min

Remarks: Based on data from similar materials

Graphite:

Toxicity to fish LL50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

: EL50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): >

100 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,012.5 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Copper metal powder:

Toxicity to fish : LC50: > 10 - 100 μg/l

Exposure time: 96 h

Toxicity to fish (Chronic tox-

: NOEC: > 1 - 10 μg/l

icity) Talc:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l

Exposure time: 24 h

Dilithium azelate:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic : NOEC (Pseudokirchneriella subcapitata (green algae)): > 1



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

plants

Exposure time: 72 h

Remarks: Based on data from similar materials

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Remarks: Based on data from similar materials

Dolomite:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): > 16.6 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility. Based on data from similar materials

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 16.6 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: No toxicity at the limit of solubility. Based on data from similar materials

Toxicity to algae/aquatic

plants

: NOEC (Desmodesmus subspicatus (green algae)): 14 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony:

aquatic invertebrates (Chron-

ic toxicity)

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 0.02 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Ecotoxicology Assessment

Chronic aquatic toxicity Very toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

Calcium oxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

: ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

Remarks: Based on data from similar materials

EC10 (Pseudokirchneriella subcapitata (green algae)): > 1

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aguatic invertebrates (Chron-

ic toxicity)

NOEC (Crangon crangon (shrimp)): > 1 mg/l

Exposure time: 14 d

Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

aquatic invertebrates (Chron-

ic toxicity)

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 0.02 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity Very toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

Quartz:

Ecotoxicology Assessment

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Toxicity to daphnia and other:

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 45 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

: LL50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): > 1

mg/l



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,000 mg/l

Exposure time: 3 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 209

Benzenesulphonic acid, propenated, calcium salts, overbased:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

: NOELR (Pseudokirchneriella subcapitata (green algae)): 100

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

: EC50: > 100 mg/l Toxicity to microorganisms

Exposure time: 8 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Persistence and degradability

Product:

Biodegradability Result: Readily biodegradable.

Remarks: Based on data from similar materials

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability Result: Not readily biodegradable.

> Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Distillates (petroleum), hydrotreated heavy naphthenic:

Biodegradability Result: Not readily biodegradable.

Biodegradation: 2 - 4 % Exposure time: 28 d

Method: OECD Test Guideline 301B



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

Dilithium azelate:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 83 % Exposure time: 30 d

Method: OECD Test Guideline 301D

Remarks: Based on data from similar materials

Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony:

Biodegradability : Result: Not readily biodegradable.

Remarks: Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 20 % Exposure time: 28 d

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Benzenesulphonic acid, propenated, calcium salts, overbased:

Biodegradability : Result: Not readily biodegradable.

Method: OECD Test Guideline 301D

Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

Dilithium azelate:

Partition coefficient: n- : log Pow: -3.53

octanol/water

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Partition coefficient: n- : log Pow: > 6.5

octanol/water Method: OECD Test Guideline 117

Benzenesulphonic acid, propenated, calcium salts, overbased:

Partition coefficient: n- : log Pow: > 4

octanol/water Remarks: Expert judgment

Mobility in soil

No data available

Other adverse effects

No data available



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues Dispose of in accordance with local regulations.

Contaminated packaging Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or

death.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number UN 3077

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Copper metal powder, Antimony, dialkyl dithiocarbamate) q

Class Packing group Ш

Labels 9

IATA-DGR

UN 3077 UN/ID No.

Proper shipping name Environmentally hazardous substance, solid, n.o.s.

(Copper metal powder, Antimony, dialkyl dithiocarbamate)

Class 9

Packing group Ш

Miscellaneous, Labels 956

Packing instruction (cargo

aircraft)

Packing instruction (passen-956

ger aircraft)

Environmentally hazardous : yes

IMDG-Code

UN number UN 3077

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Copper metal powder, Antimony, dialkyl dithiocarbamate)

Class

ENVIRONM. Subsidiary risk

Packing group

9 (ENVIRONM.) Labels

EmS Code F-A, S-F Marine pollutant yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

49 CFR

Not regulated as a dangerous good

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Copper metal powder	7440-50-8	5000	43365
Hydrogen sulfide	7783-06-4	100	182481
Ammonia	7664-41-7	100	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Hydrogen sulfide	7783-06-4	100	182481
Hydrogen sulfide Ammonia	7664-41-7	100	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Copper metal powder 7440-50-8 \Rightarrow 10 - < 20 % powder 745991-76-1 \Rightarrow 15991-76-1 \Rightarrow 1 - < 5 % ethylhex-yl)dithiocarbamat o-S,S'] antimony 75890-25-2 \Rightarrow 1 - < 5 %

dithiocarbamate

US State Regulations

Pennsylvania Right To Know

Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5
Graphite 7782-42-5



COPPER SUPREME SPECIAL BLEND®

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2019
13.0	05/06/2020	115189-00020	Date of first issue: 05/12/2015

Copper metal powder	7440-50-8
Talc	14807-96-6
Hydroxystearate sebacate lithium complexes	68815-49-6
Dilithium azelate	38900-29-7
Water	7732-18-5
Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony	15991-76-1
Calcium oxide	1305-78-8
Antimony, dialkyl dithiocarbamate	15890-25-2
Quartz	14808-60-7
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	68649-42-3
Hydrogen sulfide	7783-06-4
Ammonia	7664-41-7

California Prop. 65

WARNING: This product can expose you to chemicals including Quartz, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Graphite	7782-42-5
Copper metal powder	7440-50-8
Talc	14807-96-6
Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony	15991-76-1
Calcium oxide	1305-78-8
Antimony, dialkyl dithiocarbamate	15890-25-2

California Permissible Exposure Limits for Chemical Contaminants

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Graphite	7782-42-5
Copper metal powder	7440-50-8
Talc	14807-96-6
Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony	15991-76-1
Calcium oxide	1305-78-8
Antimony, dialkyl dithiocarbamate	15890-25-2
Quartz	14808-60-7

California Regulated Carcinogens

Quartz 14808-60-7

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

AICS : All ingredients listed or exempt.

SECTION 16. OTHER INFORMATION


Further information



COPPER SUPREME SPECIAL BLEND®

Version Revision Date: SDS Number: Date of last issue: 04/11/2019 13.0 05/06/2020 115189-00020 Date of first issue: 05/12/2015

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Pre-



COPPER SUPREME SPECIAL BLEND®

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/11/2019

 13.0
 05/06/2020
 115189-00020
 Date of first issue: 05/12/2015

vention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to

compile the Material Safety

Data Sheet

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 05/06/2020

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8