



Product # 5250

Technical Data Report

LEFT HOOK

ELECTRONIC CLEANER



DESCRIPTION

LEFT HOOK is a high purity, high dielectric, rapidly evaporating, non-flammable spray specially formulated for removing oil, grease, condensation and other contaminants from sophisticated electronic parts. Ideal for removing grease and dirt from sensitive electronics, televisions and telephone equipment.

*Quick drying formula will not harm Neoprene, Buna, Silicone, Butyl, Natural Rubber, Hypalon, PTFE, Styrene, Polystyrene, Polyethylene, Polypropylene, Epoxy, ABS, Nylon, PVC and Polyurethane.

APPLICATIONS

For use on circuit boards, terminals, relays, switches, contacts, circuit breakers, tuners, control panels, motors and other electronic equipment.

FEATURES & BENEFITS

- No Citrus Oil
- Fast Drying
- Safe on Most Plastics*, Paints, Rubber & Electronic Insulation
- Non-Flammable
- Residue Free
- Low Odor

SPECIFICATIONS

FORM: Solvent-Based Aerosol
ODOR: Ethereal Solvent
COLOR: Colorless
DETERGENCY: Excellent
TOXICITY: 200 PPM OSHA PEL
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 year
COLD STABILITY: 32°F
PHOSPHATES: None

FLASH POINT: N/D
FLAME EXTENSION: None
SOLUBILITY IN WATER: Non-Soluble
SPECIFIC GRAVITY: 1.285
% VOC: 8%
pH: N/A
PROPELLANT: 134a
EVAPORATION RATE: Fast
BIODEGRADABILITY: No

LABEL INFORMATION

LEFT HOOK ELECTRONIC CLEANER

LEFT HOOK is a high purity, high dielectric, rapidly evaporating, non-flammable spray specially formulated for removing oil, grease, condensation and other contaminants from sophisticated electronic parts. Ideal for removing grease and dirt from sensitive electronics, televisions and telephone equipment.

*Quick drying formula will not harm Neoprene, Buna, Silicone, Butyl, Natural Rubber, Hypalon, PTFE, Styrene, Polystyrene, Polyethylene, Polypropylene, Epoxy, ABS, Nylon, PVC and Polyurethane.

FOR USE ON: Circuit boards, terminals, relays, switches, contacts, circuit breakers, tuners, control panels, motors and other electronic equipment.

DIRECTIONS FOR USE: Spray directly onto surface, holding can close to work. For hard to reach areas, insert extension tube into actuator orifice. Allow components to dry completely before applying current.

DANGER: Contains gas under pressure; May explode if heated. Causes serious eye irritation. Causes damage to organs through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child. May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention if you feel unwell. Do not breathe fumes, mist, vapors, and spray. If swallowed: Immediately call a poison center or doctor. Do not induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.

WARNING: This product contains chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

CONTAINS (CAS#): 1, 1, 1, 2, 2, 3, 4, 5, 5, 5-Decafluoropentane (138495-42-8), 1,1,1,2-Tetrafluoroethane (811-97-2), Trans, 1,2 Dichloroethylene (156-60-5), Ethyl Alcohol (64-17-5) and Hexane (110-54-3).

HEALTH	1
FLAMMABILITY	1
REACTIVITY	1
PERSONAL	B



PACKAGING INFORMATION

12 – 16 oz. cans per case, 10 oz. net weight