

QuestSpecialty

SPRAYS
RIGHTSIDE UP
NMOO 3D1S1N

Mr. Mechanic
Penetrating Lubricant

Mr. Mechanic

Penetrating Lubricant

Lubricante Penetrante
Four Way Protection
Cleans, Lubricates
Prevents Rust

DANGER/PELIGRO:
EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS
UNDER PRESSURE. MAY EXPLODE IF HEATED.
AEROSOL EXTREMADAMENTE INFLAMABLE.
CONTIENE GAS A PRESION.
PUEDA EXPLOTAR SI SE CALIENTA.

NET WT. 12 OZ. (340 g)

QuestSpecialty Corporation
P.O. Box 624 • Brenham, TX 77834
713.896.6168

Will loosen dirt and scale from painted and plated surfaces. Remove loosened scale and spray again to cover surface.

TO LOOSEN BOUND PARTS: Liberal application will loosen threads, tighten fitted parts, sliding and rotating parts, bolts, hinges and pins which have been "frozen" by corrosion. Protects against renewed corrosion. This product forms a powerful, multiple-action protective shield against the harmful effects of moisture and corrosion. It protects electrical gear, metal and other surfaces from deterioration by displacing water and moisture. It seals all surfaces with a complete molecular film. It preserves equipment, thus reducing repair and maintenance costs. Lubricates, loosens dirt, scale and other corrosive elements; never becomes dry, brittle or hard. Protects the properties of insulating substances and does away with wicking. The conductivity of commutators and contacts is protected. Can be used on either dry or wet surfaces. To insure adequate protection, periodic checks should be made to determine the need for reapplication.

DIRECTIONS FOR USE: Spray liberally directly on areas to be treated. Reapply periodically as required.

MODO DE EMPLEO: Rocíe libremente el área que será tratada. Repita periódicamente según se requiera.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. —No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. If swallowed, immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.



PELIGRO: Aerosol Extremadamente Inflamable. Contiene gas a presión. Puede explotar si se calienta. Puede ser fatal en caso de ingestión y entra por las vías respiratorias.

Mantenga lejos de calor, chispas, llamas abiertas, y superficies calientes. —No fumar. No pulverice en llamas abiertas u otra fuente de ignición. Envase presurizado. No perforo ni quemé, incluso después de usar. Este producto forma un poderoso escudo de acción múltiple que protege de la luz solar. No exponga a temperaturas que excedan 50°C/122°F. Almacene en un lugar bien ventilado. Lávese bien las manos después de manipular. Si se ingiere: Láreme inmediatamente a un centro de control de venenos o a un médico. NO induzca vomito. Almacene bajo llaves. Elimine el contenido y envase de acuerdo con las ordenanzas locales, estatales, y reglamentos nacionales.

WARNING: This product can expose you to chemicals including Cumene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

ADVERTENCIA: Este producto puede exponerlo a sustancias químicas, incluyendo cumeno, que es conocido en el estado de California como causante de cáncer. Para obtener más información vaya a www.P65Warnings.ca.gov.

INGREDIENTS (CAS#): Mineral Seal Oil (64741-44-2), Petroleum Distillates, hydro-treated light (64742-47-8), Propane/n-Butane (66476-86-8), Distillates (Petroleum) solvent dewaxed, heavy paraffinic (64742-56-8), Ethyl Acetate (141-78-6).

HMIS Ratings: Health 1, Flammability 3, Reactivity 0, Personal Protection A.



ITEM 534000001-16AR

Made in USA

60000534