

LI-ION RECHARGEABLE

XPR-5592GX / XPR-5592GCX

INTRINSICALLY SAFE SCENE LIGHT

**NIGHTSTICK**  
Life Depends on Light™

## MAGNETIC MOUNT

Non-marring rubber covered base positions light for **360° rotation** and **holds firm**.



**Steel-reinforced carry handle** also functions as convenient mounting hook where needed.



Blow-molded case  
(included)



**Locking cam** allows carry handle to telescope to ideal length and position.



**Large adjustment knobs** means light can be positioned and secured for hands-free work.



**Sealed switch and charging port cap** ensure full IP-67 waterproof & dust-proof protection.

Also available as a kit with 6 foot tripod and blow-molded case. (XPR-5592GCX)

**1200 LUMENS**



1-800-233-2155 • 1-469-326-9400 • [nightstick.com](http://nightstick.com)

INTRINSICALLY SAFE

# SCENE LIGHT

LI-ION RECHARGEABLE

## ITEM NUMBER/UPC

XPR-5592GX - 017398807005  
XPR-5592GCX - 017398807012

## CERTIFICATIONS

- ATEX, IECEx, InMetro, CE, BC, cULus, UKCA
- Meets requirements of NFPA 1971-8.6 (2013)

## CASE MATERIAL

- Glass-filled nylon polymer
- Serialized for personal identification

## LUMENS/RUNTIME

- HIGH: 1200L, 6 hrs. runtime
- LOW: 650L, 12 hrs. runtime

## WATER RATING

- IP-67 (dust-proof, waterproof)

## DROP RATING

- 2 meters

## DIMENSIONS

- LENGTH: 13.5 in (343mm)
- WIDTH: 9.25 (235mm)
- DEPTH: 3.5 in (89mm)
- WEIGHT: 4 lbs 4 oz (1,928g)

## BATTERY

- Integrated rechargeable li-ion battery

## WARRANTY

- 1 Year limited warranty

## WHAT'S INCLUDED

XPR-5592GX

- Scene Light
- AC & DC charging cords
- Blow-molded case

XPR-5592GCX

- Scene Light
- 6 foot tripod
- AC & DC charging cords
- Blow-molded case

**NIGHTSTICK®**  
XPR-5592GX



E 467756  
ID 4003544  
ELECTRICAL SAFETY  
INTRINSICALLY SAFE  
SECURITE INTRINSEQUE

Bayco Products, Inc.  
640 S. Sanden Blvd., Wylie, TX 75098

FLOODLIGHT FOR USE IN HAZARDOUS LOCATIONS  
For use with Bayco Li-ion Battery Pack 5592-BATT only

CLASS I DIV 1 GRPS A-D T4 CLASS II & III DIV1 GRPS E-G T135°C CLASS I ZONE 0 GROUP IIC T4 Ga  
60/11 1G Ex ia op is IIC T4 Ga  
5592-BATT 3.7V/Cell Li-ion Um 10V

WARNING: Do not charge battery in a hazardous location  
WARNING: Do not replace battery when an explosive atmosphere is present  
SEE INSTRUCTION MANUAL US Patents 10,879,518 & 11,450,854  
VOIR MANUEL ATEX 19 ATEX 2189 UL220UEX2429 IECEx UL 19.0013  
ATENÇÃO - VER MANUAL DE INSTRUÇÕES IECEx UL 19.0013  
5592-BATT 3.7V/Cell Li-ion Um 10V

Meets Requirements of NFPA-1971-8.6 (2013)



### CERTIFIED

