

LI-ION RECHARGEABLE

NSR-9940XL

DUTY/PERSONAL-SIZE FLASHLIGHT

NIGHTSTICK[®]
Life Depends on Light

**DUAL
LIGHT
TECHNOLOGY**



Downward facing floodlight provides soft, unfocused light for reading or walking, or added safety in Dual-Light™ mode.



Powerful integrated **Tail cap magnet** for hands-free use.



Light includes **drop-in charger** designed to be mounted to wall or dashboard with included AC/DC adapters.



Constructed of 6061-T6 **anodized aluminum** with aggressive knurling for positive grip.



1100 LUMENS

1-800-233-2155 • 1-469-326-9400 • nightstick.com

©2020 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

DUTY/PERSONAL FLASHLIGHT

LI-ION RECHARGEABLE

ITEM NUMBER/UPC

- NSR-9940XL, UPC 0 17398 80411 0
- NSR-9940XL-BL, UPC 0 17398 80745 6
- NSR-9940XL-R, UPC 0 17398 80744 9
- NSR-9940XL-G, UPC 0 17398 80746 3

MARKET APPLICATIONS

- Law enforcement, security, sporting goods, fire, rescue, industrial and automotive

CERTIFICATIONS

- CE, CEC, BIS,
- US Patent: 9,713,217

CASE MATERIAL

- Aircraft-grade 6061-T6 Aluminum w/Type III Hard Anodized Finish

LUMENS/RUNTIME

FLASHLIGHT

- HIGH: 1100L, 4.25 hrs. runtime
- MEDIUM: 500L, 16 hrs. runtime
- LOW: 300L, 40 hrs. runtime

FLOODLIGHT

- HIGH: 250L, 12 hrs. runtime

DUAL-LIGHT

- 800L, 6 hrs. runtime

CANDELA

- HIGH: 29,033
- MEDIUM: 12,014
- LOW: 7,296

BEAM DISTANCE

- HIGH: 341m
- MEDIUM: 219m
- LOW: 171m

WATER RATING

- IP-X7 Waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 9.5 in (241 mm)
- HANDLE DIAMETER: 1.2 in (30 mm)
- HEAD DIAMETER: 1.6 in (41 mm)
- WEIGHT: 13.2 oz (374 g)

BATTERY









- Rechargeable Lithium-ion

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Flashlight
- Anti-roll Ring
- Rechargeable Lithium-ion Battery
- AC Power Supply
- DC Power Supply and Charger
- Instruction manual

FL1 STANDARD	SPOT HIGH	FLOOD HIGH	DUAL-LIGHT
	1100 LUMENS	250 LUMENS	800 LUMENS
	4h 25min	12h	6h
	350m		
	30625cd		
			
<div>CERTIFIED</div> <div>    </div>			