

LI-ION RECHARGEABLE

NSR-9614XL

DUTY/PERSONAL-SIZE FLASHLIGHT

**NIGHTSTICK**  
Life Depends on Light™



**Momentary/constant-on tail switch** for overhead use or in combination with handgun.



**Mountable drop-in charging base** comes with AC and DC cords for use at home or in a vehicle.



**850-lumen bright white LED** paired with optimized reflector creates a tight, focused beam.



**6061-T6 aluminum body** features aggressive machined knurling for a positive grip in all conditions.

CERTIFIED



NFPA

850 LUMENS

1-800-233-2155 · 1-469-326-9400 · [nightstick.com](http://nightstick.com)

# DUTY/PERSONAL FLASHLIGHT

## LI-ION RECHARGEABLE

### ITEM NUMBER/UPC

- NSR-9614XL, UPC 017398802178

### MARKET APPLICATIONS

- Law enforcement, security, sporting goods, fire, rescue, industrial and automotive

### CERTIFICATIONS

- CE, CEC, BIS, NFPA-1971-8.6 (2018), NFPA 1900-11.1.11.2 (2024)

mounted in any position

### CASE MATERIAL

- 6061-T6 Aluminum

### LUMENS/RUNTIME

- HIGH: 850L, 6.5 hrs. runtime  
- MEDIUM: 200L, 9 hrs. runtime  
- LOW: 50L, 50 hrs. runtime

### STROBE RUNTIME

- 5.5 hrs. runtime

### CANDELA

- HIGH: 23,976  
- MEDIUM: 12,075  
- LOW: 6,200

### BEAM DISTANCE

- HIGH: 325m  
- MEDIUM: 166m  
- LOW: 85m

### WATER RATING

- IP-X7 Waterproof

### DROP RATING

- 2 meters

### DIMENSIONS

- LENGTH: 8.9 in (226 mm)  
- HANDLE DIAMETER: 1.2 in (30 mm)  
- HEAD DIAMETER: 1.6 in (41 mm)  
- WEIGHT: 12.8 oz (363 g)

### BATTERY






- Rechargeable Lithium-ion

### WARRANTY

- Limited lifetime warranty

### WHAT'S INCLUDED

- Flashlight  
- Anti-roll Ring  
- Rechargeable Lithium-ion Battery  
- AC Power Supply  
- DC Power Supply and Charger  
- Instruction manual

| FL 1 STANDARD   | SPOT HIGH      | SPOT MEDIUM   | SPOT LOW      |
|---|----------------|---------------|---------------|
|  | 1100<br>LUMENS | 500<br>LUMENS | 125<br>LUMENS |
|  | 6h 30min       | 15h           | 60h           |
|  | 350m           | 232m          | 114m          |
|  | 30625cd        | 13439cd       | 3275cd        |
|  |                |               |               |

#### CERTIFIED



NFPA