Safety Data Sheet



Revision Number: 008.0

1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

Product name:

Product type: Sealar Restriction of Use: None Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

LOCTITE SI 596 RD known as LOCTITE SUPERFLEX RED RTV 80ML Sealant None identified

 Item number:
 59630

 Region:
 United States

 Contact information:
 United States

 Telephone: +1 (860) 571-5100
 MEDICAL EMERGENCY Phone: Poison Control Center

 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC

 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

135507

2. HAZARDS IDENTIFICATION

DANGER:

EMERGENCY OVERVIEW CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE DAMAGE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1
PICTOGRAM(S)	

Precautionary Statements

Prevention:	Wash affected area thoroughly after handling. Wear protective gloves, eye protection, and face protection.
Response:	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. Take off contaminated clothing.
Storage:	Not prescribed
Disposal:	Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS			
Hazardous Component(s)	CAS Number	Percentage*	
Distillates (petroleum), hydrotreated middle	64742-46-7	5 - 10	
Silicon dioxide	7631-86-9	5 - 10	
Methylsilanetriyl triacetate	4253-34-3	1 - 5	

IDH number: 135507

Product name: LOCTITE SI 596 RD known as LOCTITE SUPERFLEX RED RTV 80ML Page 1 of 6

Triacetoxyethylsilane	17689-77-9	1 - 5
Acetic acid	64-19-7	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES			
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention		
Skin contact:	Wipe off paste with paper towel or cloth. Wash with soap and water. If skin irritation persists, call a physician.		
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least minutes. If eye irritation persists, consult a specialist.		
Ingestion:	Do not induce vomiting. If a person feels unwell or symptoms of skin irritation appear, consult a physician.		
Symptoms:	See Section 11.		
Notes to physician:	Treat symptomatically.		
5. F	IRE FIGHTING MEASURES		
Extinguishing media:	Foam, dry chemical or carbon dioxide.		
Special firefighting procedures:	None		
Unusual fire or explosion hazards:	None		
Hazardous combustion products:	Silica mist. Formaldehyde. Acrid smoke and fumes.		

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

7 ΗΔΝΓ	DLING AND STORAGE
Clean-up methods:	Maintain good ventilation for large spills. Store in a partly filled, closed container until disposal. Spilled material will solidify. Scrape up as much material as possible.
Environmental precautions:	Do not allow product to enter sewer or waterways.

Storage:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container closed. Store in a dry area below 90° F.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated middle	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 PEL Mist.	None	None
Silicon dioxide	6 mg/m3 TWA	20 MPPCF TWA 0.8 mg/m3 TWA	None	3 mg/m3 TWA Respirable fraction.
Methylsilanetriyl triacetate	None	None	None	None
Triacetoxyethylsilane	None	None	None	None
Acetic acid	15 ppm STEL 10 ppm TWA	10 ppm (25 mg/m3) PEL	None	None

Engineering controls:

Use only with adequate ventilation.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure

Eye/face protection:

Skin protection:

limit(s). Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Use impermeable gloves and protective clothing as necessary to prevent skin

9. PHYSICAL AND CHEMICAL PROPERTIES

contact.

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Flammability: Evaporation rate: Solubility in water: Solubility in water: Partition coefficient (n-octanol/water): VOC content:

Viscosity: Decomposition temperature:

Liquid, Paste Red Acetic acid Not available. Not applicable 13 hPa (21 °C (69.8 °F)) Not available. Not available. 1.01 at 20 °C (68°F) Heavier than air. > 93 °C (> 199.4 °F) 4 % (acetic acid) 19.9 % (acetic acid) Not available. Not applicable Not available. Not soluble. Polymerizes in presence of water. Not determined Not available. 3.08 %; 32 g/l Not available. Not available. Not available.

	10. STABILITY AND REACTIVITY
Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Acetic acid is liberated slowly upon contact with moisture. Formaldehyde. Irritating vapors.
Incompatible materials:	Acids. Water Bases. Oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Exposure to moisture. Prolonged heating at temperatures above 150 °C.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Acetic acid produced during cure may irritate eyes, nose and throat. When heated to
temperatures exceeding 300° F (150° C) in the presence of air, silicones may form
formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit.
Causes skin irritation.
Causes serious eye damage.
Not expected under normal conditions of use. May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Distillates (petroleum), hydrotreated middle	None	Irritant Nuisance dust	
Silicon dioxide	Oral LD50 (Rat) = > 22,500 mg/kg Oral LD50 (Mouse) = > 15,000 mg/kg		
Methylsilanetriyl triacetate	None	Irritant, Allergen	
Triacetoxyethylsilane	None	No Target Organs	
Acetic acid	Oral LD50 (Rabbit) = 1,200 mg/kg Oral LD50 (Mouse) = 4,960 mg/kg Oral LD50 (Rat) = 3.53 g/kg Oral LD50 (Rat) = 3.31 g/kg Dermal LD50 (Rabbit) = 1,060 mg/kg Inhalation LC50 (Rat, 4 h) = 11.4 mg/l	Allergen, Corrosive, Eyes, Gastrointestinal, Immune system, Irritant, Kidney	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated middle	No	No	No
Silicon dioxide	No	No	No
Methylsilanetriyl triacetate	No	No	No
Triacetoxyethylsilane	No	No	No
Acetic acid	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:	Follow all local, state, federal and provincial regulations for disposal. Cured rubber can be incinerated or landfilled following EPA and local regulations.
Hazardous waste number:	This product may contain traces of: D005. Barium. D007. Chromium. D004: Arsenic However this product is only classifiable as hazardous waste if it exhibits the characteristics of toxicity as shown by the toxicity characteristic leaching procedure (TCLP). Under RCRA, it is the responsibility of the end user of this product to determine whether it meets this criteria at the time of disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (4	19 CFR)
Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
International Air Transportation (ICAO/IATA)	
Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
Water Transportation (IMO/IMDG)	
Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health None above reporting de minimis.
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2, 11

IDH number: 135507

Product name: LOCTITE SI 596 RD known as LOCTITE SUPERFLEX RED RTV 80ML Page 5 of 6

Prepared by: Product Safety and Regulatory Affairs

Issue date: 01/26/2018

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.