Safety Data Sheet



Revision Number: 007.0 Issue date: 10/05/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: **LOCTITE 243 THREADLOCKER 50ML** Product type: Threadlocker Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

WARNING:

IDH number: 1329467 Item number: 1329467 **United States** Region:

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www henkelna com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION. SUSPECTED OF CAUSING CANCER.

| HAZARD CLASS | HAZARD CATEGORY |
|--------------------|-----------------|
| SKIN IRRITATION | 2 |
| EYE IRRITATION | 2A |
| SKIN SENSITIZATION | 1 |
| CARCINOGENICITY | 2 |





Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear

protective gloves, clothing, eye and face protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye

irritation persists: Get medical attention. Take off contaminated clothing.

Storage: Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* | |
|-------------------------------|------------|-------------|--|
| Tetramethylene dimethacrylate | 2082-81-7 | 20 - 30 | |
| Amorphous fumed silica | 68611-44-9 | 1 - 5 | |
| Ethene, homopolymer | 9002-88-4 | 1 - 5 | |
| Propane-1,2-diol | 57-55-6 | 1 - 5 | |
| Cumene hydroperoxide | 80-15-9 | 0.1 - 1 | |
| 1-Acetyl-2-phenylhydrazine | 114-83-0 | 0.1 - 1 | |
| Cumene | 98-82-8 | 0.1 - 1 | |

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. Get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). Wash clothing before reuse. Get

medical attention.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical

attention.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Uncontrolled polymerization may occur at high temperatures resulting in

explosions or rupture of storage containers.

Hazardous combustion products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic

fragments.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to

prevent entry into water system; wear full protective equipment during cleanup. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until

disposal.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Keep container closed. Use only with

adequate ventilation. Refer to Section 8.

Storage: For safe storage, store at or below 38 °C (100.4 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|-------------------------------|--|--|---------------------------------------|-------|
| Tetramethylene dimethacrylate | None | None | None | None |
| Amorphous fumed silica | None | 0.8 mg/m3 TWA 20 MPPCF TWA | None | None |
| Ethene, homopolymer | 10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles. | 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. | None | None |
| Propane-1,2-diol | None | None | 10 mg/m3 TWA Aerosol. | None |
| Cumene hydroperoxide | None | None | 1 ppm (6 mg/m3) None TWA (SKIN) | |
| 1-Acetyl-2-phenylhydrazine | None | None | None | None |
| Cumene | 50 ppm TWA | 50 ppm (245 mg/m3) PEL (SKIN) | None | None |

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Butyl rubber gloves. Neoprene

gloves. Natural rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: LiquidLiquid
Color: BlueBlue

Odor: CharacteristicCharacteristic

Odor threshold: Not available. pH: Not available.

Vapor pressure: $< 0.1 \text{ mm hg} (27 \,^{\circ}\text{C} (80.6 \,^{\circ}\text{F}))$ Boiling point/range: $> 149 \,^{\circ}\text{C} (> 300.2 \,^{\circ}\text{F})$

Melting point/ range: Not available.

Specific gravity: 1.09

Vapor density:Not available.Flash point:> 93 °C (> 199.4 °F)Flammable/Explosive limits - lower:Not available.

Flammable/Explosive limits - upper:

Autoignition temperature:

Flammability:

Evaporation rate:

Solubility in water:

Not available.

Not applicable

Not available.

Slight

Partition coefficient (n-octanol/water):

VOC content:

Viscosity:

Not available.

Not available.

Not available.

Not available.

Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing. Polymerization may occur at elevated temperature or in the

presence of incompatible materials.

Hazardous decomposition

products:

IDH number: 1329467

Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Irritating organic fragments.

Incompatible materials: Strong oxidizing agents. Reducing agents. Strong alkalis. Oxygen scavengers. Other

polymerization initiators. Heavy metals.

Reactivity: Not available.

Conditions to avoid: Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from

incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: Inhalation of vapors or mists of the product may be irritating to the respiratory system.

Skin contact: Causes skin irritation. May cause allergic skin reaction.

Eye contact: Causes serious eye irritation.

Ingestion: May cause gastrointestinal tract irritation if swallowed.

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects | |
|-------------------------------|---|--|--|
| Tetramethylene dimethacrylate | None | Irritant, Allergen | |
| Amorphous fumed silica | None | No Target Organs | |
| Ethene, homopolymer | None | No Target Organs | |
| Propane-1,2-diol | Oral LD50 (Rabbit) = 18 g/kg Oral LD50 (Mouse) = 23.9 g/kg Oral LD50 (Rat) = 30 g/kg | Irritant | |
| Cumene hydroperoxide | Inhalation LC50 (Mouse, 4 h) = 200 mg/l | Allergen, Central nervous system, Corrosive, Irritant, Mutagen | |
| 1-Acetyl-2-phenylhydrazine | Oral LD50 (Mouse) = 270 mg/kg | Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity | |
| Cumene | Oral LD50 (Rat) = 2.91 g/kg Oral LD50 (Rat) = 1,400 mg/kg Inhalation LC50 (Rat, 4 h) = 8000 ppm | Central nervous system, Irritant, Lung | |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|-------------------------------|--|-----------------|---|
| Tetramethylene dimethacrylate | No | No | No |
| Amorphous fumed silica | No | No | No |
| Ethene, homopolymer | No | No | No |
| Propane-1,2-diol | No | No | No |
| Cumene hydroperoxide | No | No | No |
| 1-Acetyl-2-phenylhydrazine | No | No | No |
| Cumene | Reasonably Anticipated to be a Human Carcinogen. | Group 2B | No |

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: RQ, Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division: 9
Identification number: UN 3082

Packing group:

DOT Hazardous Substance(s): alpha,alpha-Dimethylbenzylhydroperoxide

International Air Transportation (ICAO/IATA)

Proper shipping name: RQ, Environmentally hazardous substance, liquid, n.o.s. (Fatty acid amide)

Hazard class or division: 9

Identification number: UN 3082 Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty

acid amide)

Hazard class or division: 9

Identification number: UN 3082

Packing group:

Marine pollutant: Fatty acid amide

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.
Immediate Health, Delayed Health
None above reporting de minimis.

CERCLA Reportable quantity: Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2

Prepared by: Product Safety and Regulatory Affairs

Issue date: 10/05/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.